

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO
OPERATOR

Check
Form C-101

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY

Great Western Drilling Company (Company or Operator) State CV
Well No. 3, in 2E 1/4 of E4 1/4, of Sec. 25, T. 17, R. 33-E, NMPM.
County.
Well is 1650 feet from North line and 1980 feet from West line
of Section 25. If State Land the Oil and Gas Lease No. is B-7424
Drilling Commenced June 30, 1962, 19 Drilling was Completed Aug 22, 1962, 19
Name of Drilling Contractor Great Western Drilling Company
Address Box 1659, Midland, Texas
Elevation above sea level at Top of Tubing Head 3913 The information given is to be kept confidential until

OIL SANDS OR ZONES

No. 1, from 6498 to 8940 No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None recorded to feet
No. 2, from to feet
No. 3, from to feet
No. 4, from to feet

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM
10-3/4	52	NEW	312	Tex. Pat.	None
7-5/8	24	NEW	5455	Float	None
4-1/2	11.0	NEW	5022	Float	
2	4.6	NEW	2363		

PERFORATIONS	PURPOSE
8620	8940

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHITE SET	NO. BAGS OF CEMENT	METHOD USED	MT. GRAVITY
12-1/2	10-3/4	312	350	Pump & Plug	10.1
7-5/8	9-1/2	5455	650	Pump & Plug	9.3
6-3/4	4-1/2	5022	1199	Pump & Plug	9.1

MT. GRAVITY	AMOUNT OF MUD USED
	200 lbs.
	300 lbs.
	500 lbs.

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated)

Perforations 8620-8940 tested salt water. A cast iron bridge plug was set in the well.
Acidized with 30,000 gal. Sulfuric acid water. Pulled and packed with packer at 8915 with 3,000 gal. Acid.