

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DRAPE OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER	5a. Indicate Type of Lease State ☒ Fee ☐
2. Name of Operator Phillips Petroleum Company	5. State Oil & Gas Lease No. B2735
3. Address of Operator Room 711, Phillips Building, Odessa, Texas 79761	7. Unit Agreement Name Vacuum ABO Unit
4. Location of Well UNIT LETTER B 990 FEET FROM THE North LINE AND 1650 FEET FROM THE East LINE, SECTION 26 TOWNSHIP 17-S RANGE 35-E NMPM.	8. Farm or Lease Name Btry 4 Vacuum ABO Unit 4
10. Field and Pool, or Without Vacuum ABO Reef.	9. Well No. 6
11. Elevation (Show whether DF, RT, CR, etc.) 3918' RKB	12. County Len

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any promised work) SEE RULE 1103.

12-11-75: MI Johnson Unit. Pull rods and tbg.
12-12-75: Set 2 3/8" tbg. at 8500' W/Baker R pkr on bottom. Runco treated down tbg thru perfs 8586-8850' W/3500 gals. 28% HCL NE acid, flushed W/42 BW; Used 1 ball sealer per 2 bbls acid. Max. press. 2500#, min. O# ISDP O#. AIR 5.1 BPM. Swbd 3 1/2 hrs, 42 BLW, 10 BAW, no oil.
12-13-75: Swbd 9 hrs, 26 BO, 33 BAW.
12-14-75: SD 24 hrs.
12-15-75: Pld tbg. & pkr. Set 2 3/8" tbg. W/Baker anchor catcher OE at 8580'. Set 2" x.1 1/4" x 20' pump at 8576'. Released Johnson Unit. P/16 hrs., no gauge.
12-16-75: P/24 hrs., 27BO, 16 BSW.
12-17-75: P/24 hrs., 25 BO, 16BSW
12-18-75 P/24 hrs., perfs 8586-8850' in ABO, 28BO, 14 BSW, GOR 721/1. Restored to production.

BOP Eqpt: Series 900, 3000# WP, double W.one set pipe rams, one set blind rams, manually operated

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed W. J. Mueller TITLE Engineering Advisor DATE 12-19-75

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: