GARY W. WINK

OC FIELD REPRESENTATIVE HIGTARE MANAGED

DAJAN 3 0 2003

3 6 (This space for State use)

Conditions of approval, if any:

APPROVED BY

East Vacuum GB/SA Unit #2739-001

11/19/02: SWAB BACK TOLUENE. MADE 6 RUNS W/SWAB LINE. SWABBED BACK 16 BBLS. WELL STARTED FLOWING. FLOWED BACK 203 BBLS. TOTAL FLUID RECOVERED 219 BBLS. GIH W/3 STDS. PUMPED 500 GALLONS SCALE CONVERTER. COOH W/6 STDS, SET PKR, & TESTED CSG W/500 PSI, HELD OK.

11/20/02: RU HALLIBURTON, ROLLED CHEMICALS INTO ACID & BRINE WATER. ACIDIZED WELL W/6500 GALLONS SBM 15% FERCHECK ACID. PUMPED 50 BBLS FRESH WATER PAD. ACID STAGE #1 – 500 GALLONS ACID, 1535 PSI W/ACID IN FORMATION. BLOCK #1 (1000# TBA 110 & 1000# 100 MESH SALT), 2000# TOP PSI ON BLOCK #1. ACID STAGE #2 – 2000 GALLONS ACID, 1558 PSI W/ACID IN FORMATION. BLOCK #2 (2000# TBA 110 AND 2000# 100 MESH SALT), 2184# TOP PSI ON BLOCK #2. ACID STAGE #3 – 2000 GALLONS ACID, 1698 PSI W/ACID IN FORMATION. BLOCK #3 (3250# TBA 110 AND 3250# 100 MESH SALT), 2702# TOP PSI ON BLOCK #3. ACID STAGE #4 – 2000 GALLONS ACID, 2456 PSI W/ACID IN FORMATION. FLUSHED W/44 BBLS FRESH WATER. ISIP 1840# 5 MIN SIP 1685, 10 MIN SIP 1645, 15 MIN SIP 1612. 603 BBLS TOTAL LOAD PUMPED. SHUT IN WELL FOR 1 HOUR. OPENED UP WELL & FLOWED BACK 80 BBLS. MADE 3 SWAB RUNS. WELL SWABBED DRY.

11/21/02: SWABBED BACK WELL. MADE 12 SWAB RUNS, RECOVERED 13 BBLS. COULD NOT GET SWAB PAST 2200 FT. SALT IN TBG. WAITED ON KILL TRUCK. PUMPED 130 BBLS FRESH WATER DOWN TBG TO DISSOLVE SALT. OPENED UP WELL AND FLOWED BACK. FLOWED BACK 70 BBLS.

11/22/02: UNSET PKR & PUMPED BRINE WATER TO KILL WELL. UNABLE TO KILL WELL.

11/23/02: SHUT DOWN FOR WEEKEND.

11/24/02: SHUT DOWN FOR WEEKEND.

11/25/02: RIG REPAIR, CHANGE OUT STARTER. PUMPED BRINE WATER TO KILL WELL. COOH W/PKR & TBG, LAID DOWN PKR. GIH W/2-7/8 NOTCHED COLLAR & TBG. WASHED 50 FT OF SALT. LAID DOWN 8 JTS TBG.

11/26/02: WAIT ON KILL TRUCK. PUMPED BRINE WATER TO KILL WELL. COOH W/TBG. NIPPLED DOWN BOP & FLANGED UP WELLHEAD. CIRCULATED PKR FLUID. UNFLANGED WELLHEAD, SET PKR, FLANGED UP WELLHEAD, AND TESTED CSG W/500 PSI, HELD OK.

11/27/02: REPLACED MALLARD MOTOR VALVE W/KIMRAY MOTOR VALVE. REPLUMBED FLOWLINE. MADE 2 SWAB RUNS TO KICKOFF WELL. WELL FLOWING. RD DDU, CLEANED LOCATION. WELL BACK ON PRODUCTION. TEMPORARY DROP FROM REPORT.

12/02/02: WELL ON TEST. 33 OIL, 913 WATER, 776 GAS.

12/03/02: WELL ON TEST. 40 OIL, 868 WATER, 806 GAS.

12/04/02: NO TEST DATA AVAILABLE, TEST SEPERATOR DOWN ON HIGH PRESSURE.

12/05/02: WELL ON TEST. 88.5 OIL, 625 WATER, 728 GAS. WELL FLOWING W/300 PSI ON TBG & 150 PSI ON FLOWLINE. COMPLETE DROP FROM REPORT.