

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

| | |
|------------------------|--|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | |

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

API NO. 30-025-02898

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL
WELL ☒

GAS
WELL ☐

OTHER-

Name of Operator

Phillips Petroleum Company

Address of Operator

RM 401, 4001 Penbrook St., Odessa, TX 79762

Location of Well

UNIT LETTER L, 1980' FEET FROM THE South LINE AND 660' FEET FROM
THE West LINE, SECTION 27 TOWNSHIP 17-S RANGE 35-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3943' RKB

5a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

B-1840

7. Unit Agreement Name

East Vacuum Gb/SA Unit

8. Farm or Lease Name

East Vacuum Gb/SA Unit

9. Well No. Tract 2739

004

10. Field and Pool, or Whidcat

Vacuum Gb/SA

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

REMEDIAL WORK ☒

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-20 thru

3-24-86: RU DDU. Reda pmp stuck. Changed out wellhead. NU BOP. Spt'd Unichem 405 converter. S.D. Pmpd 500 gals of 15% NEFE HCL acid, displaced w/76BFW. Worked tbg loose displaced remainder of acid into O.H. COOH w/tbg & pmp.

3-25-86: WIH w/4-7/8" bit, Dc's on 2-7/8" tbg. Cleaned out from 4220-'4580'. COOH w/tbg, DC. WIH w/5 1/2" pkr, spt'd 8 drums of Unichem 405 scale converter across O.H. 4220-'4580'.

3-26-86: Acidized OH from 4220' to 4580' w/3000 gals 15% NEFE HCL w/3 drums of Techniclean 425 & 3 drums of Techni-hib 756 scale inhibitor.

3-27-thru

3-30-86: WIH w/Reda pmp on 2-3/8" tbg, set bottom of motor @ 4178'. Pmpd 14 hrs, no test. Pmpd 48 hrs, rec 148 BO, 12 MCFG, 2824 BW.

3-31-86: Pmpd 24 hrs, 72 BO, 6MCFG, 1371 BW, GOR 83 from OH 4220-'4597'. Job Complete.

16. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

W. J. Mueller

TITLE Engineering Supervisor

DATE April 11, 1986

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

APR 15 1986

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
APR 14 1986
O.C.D.
HOBBS OFFICE