

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5a. Indicate Type of Lease State ☒ Fee ☐
2. Name of Operator Phillips Petroleum Company		5. State Oil & Gas Lease No. B-1840
3. Address of Operator Room 711, Phillips Bldg., Odessa, Texas 79761		7. Unit Agreement Name Vacuum Abo Unit
4. Location of Well UNIT LETTER 0 330 FEET FROM THE south LINE AND 1650 FEET FROM THE east LINE, SECTION 27 TOWNSHIP 17S RANGE 35E NMPM		8. Form or Lease Name Btry 4 Vacuum Abo Unit, Tract 1
15. Elevation (Show whether DF, RT, GR, etc.) 3940' RKB		9. Well No. 8
		10. Field and Pool, or Without Vacuum Abo Reef
		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 4-15-76: MI Well Units WS unit, Pulled 2-3/8" tbg, Guiberson RMC-1 pkr and fluid pac bottom hole assy. Ran tbg w/Kobe bottom hole assy and Guiberson RMC-1 pkr set at 8413', Kobe bottom hole assy at 8404', intake at 8413'. Filled hole w/150 BO. Dropped 2" x 1-3/8" Kobe "E" pump. P/15 hrs, 220 BO, 188 BSW, 37 SPM at 3350#.
- 4-16-76: P/24 hrs, 368 BO, 289 BSW, GOR 1383/1.
- 4-17-76: P/24 hrs, 388 BO, 296 BSW, GOR 1577/1.
- 4-18-76: P/24 hrs, 367 BO, 298 BSW.
- 4-19-76: P/24 hrs, 409 BO, 322 BSW.
- 4-20-76: P/24 hrs, 417 BO, 408 BSW, GOR 1721/1, W/2" x 1-3/8" Kobe E pump; perfs 8445-8737. Restored to production.

BOP Eqpt: Series 900, 3000# WP, double w/one set blind rams, one set pipe rams, manually operated.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller TITLE Engineering Advisor DATE 4-22-76

APPROVED BY DATE 2 28 1976

CONDITIONS OF APPROVAL, IF ANY: