NEW M ACOURTON	NSERVATION COMMIS ON RECEIVED	N ILLAND
MISCELLANI	FOUS NOTICES \ MAY 1	5 1951
Submit this notice in trip cate to the Oil Conservation Conservation. A copy will be rejurned to the sender on which advisable, or the rejection by the Commission or agent, of and work should not begin until approval is obtained. The Commission.	ommission or its proper agent before the work spec	RADING CHIMPS IN
Indicate nature of r	notice by checking below:	
VOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	x
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		
	S. How Kerico Key 14, 19	951
	Place Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico		
Gentlemen:		
Following is a notice of intention to do certain work as c		
Standard O11 Gengany Of Texas St Company or Operator Lease	Well Noin	SW 1/4 01
of Sec27, T17-8, R35-1	, N. M. P. M.,	Field.
County.		
County.		
FULL DETAILS OF PR	ROPOSED PLAN OF WORK	
FULL DETAILS OF PF FOLLOW INSTRUCTIONS IN THE RULE	ES AND REGULATIONS OF THE COMMISSION	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE To bridg pluggest at 4270', fill with gar	es and regulations of the commission rel to 4265' fill with Calson to 425	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 524 154 f flush joint casing	es and regulations of the commission rel to 4265' fill with Calseal to 425' cement easing with 250 seeks of cement	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE To bridg pluggest at 4270', fill with gar	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 53° 15° f flush joint casing Mill out coment and plug close out to tot	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 53° 15° f flush joint casing Mill out coment and plug close out to tot	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 53° 15° f flush joint casing Mill out coment and plug close out to tot	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 53° 15° f flush joint casing Mill out coment and plug close out to tot	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 53° 15° f flush joint casing Mill out coment and plug close out to tot	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 53° 15° f flush joint casing Mill out coment and plug close out to tot	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE IN Bridg pluggest at 4270', fill with gav In 4245' of 53° 15° f flush joint casing Mill out coment and plug close out to tot	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE TO Dridg pluggest at 4270', fill with gav In 4245' of 54" 154 # flush joint casing Fill out coment and plug close out to tot In radioactivity log and put well back on	es and regulations of the commission rel to 4265' fill with Calson to 4250 commission of commission at the 4265' fill with 250 seeks of commission to 4265' .	
FULL DETAILS OF PERFORMANCE FOLLOW INSTRUCTIONS IN THE RULE IN 1916 pluggeof at 4270°, fill with gaven 4245° of 54° 154° filsch joint casing fill out cament and plug clean out to tot in redicactivity log and put well back on the second second put well back on the second put well ba	es and regulations of the commission rel to 4265' fill with Calseel to 429 cement easing with 250 seeks of cemental depth/654'. A production.	n t •
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE The bridg pluggest at \$270°, fill with gave in \$25° of 55° 155 ¢ flush joint casing will out coment and plug close out to tot in redisactivity log and put well back on MAY 16 '95° MAY 16 '95° MAY 16 '95° Approved	s and regulations of the commission of the 4265' fill with Calson to 425' cement ensing with 250 sacks of cemental depth/654'. Standard Cil Company of Tex	n t •
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE TO DRING Pluggeot at \$270°, fill with gav The \$245° of 54° 154° fillsh joint casing Fill out count and plug close out to tot The rediscontivity log and put well back on MAY 16 1951 MAY 16 1951	Standard Gil Gempany of Tex Company or Operator	n t •
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE The bridg pluggest at \$270°, fill with gave in \$25° of 55° 155 ¢ flush joint casing will out coment and plug close out to tot in redisactivity log and put well back on MAY 16 '95° MAY 16 '95° MAY 16 '95° Approved	Standard 611 Company of Tex Company or Operator By	n t •
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE The bridg pluggest at \$270°, fill with gave in \$25° of 55° 155 ¢ flush joint casing will out coment and plug close out to tot in redisactivity log and put well back on MAY 16 '95° MAY 16 '95° MAY 16 '95° Approved	Standard Gil Gempany of Tex Company or Operator By Position	nt.
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE The bridg pluggest at \$270°, fill with gave to \$245° of 54° 154° flush joint casing fill out cament and plug clean out to tot to redicactivity log and put well back on MAY 16 '95° Approved	Standard Oil General of Tex Company or Operator By Position Productions Forement Send communications regarding w	nt.
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE The bridg pluggest at \$270°, fill with gave in \$25° of 55° 155 ¢ flush joint casing will out coment and plug close out to tot in redisactivity log and put well back on MAY 16 '95° MAY 16 '95° MAY 16 '95° Approved	Standard Gil Gempany of Tex Company or Operator By Position	nt.
FULL DETAILS OF PE FOLLOW INSTRUCTIONS IN THE RULE The bridg pluggest at \$270°, fill with gave to \$245° of 54° 154° flush joint casing fill out cament and plug clean out to tot to redicactivity log and put well back on MAY 16 '95° Approved	Standard Cil Company of Tex Company or Operator By Position Production Production Standard Cil Company of Tex Company or Operator By Name Standard Cil Company of Tex Company or Operator By Name Standard Cil Company of Tex Company or Operator	nt.

• •

manufaction of the state of the