

OIL CONSERVATION DIVISION

P. O. BOX 2038

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API #30-025-02917

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.  
3-2224

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OFFER OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

OIL  
WELL ☒

GAS  
WELL ☐

OTHER- Re-enter to plug

Name of Operator

Phillips Petroleum Company (Santa Fe #15)

Address of Operator

4001 Penbrook, Rm 401, Odessa, Texas 79762

Location of Well

UNIT LETTER A, 660 FEET FROM THE North LINE AND 660 FEET FROM

THE East LINE, SECTION 28 TOWNSHIP 17-S RANGE 35-E NMPM.

7. Unit Agreement Name

East Vacuum Gb/SA Unit

8. Farm or Lease Name East  
Vac Gb/SA Unit Tr. 2851

9. Well No.

015

10. Field and Pool, or Wildcat

Vacuum Gb/SA

11. Elevation (Show whether DF, RT, GR, etc.)

3941.8' Gr

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

OTHER ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Replug per OCD Order R-5897 ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-22-80 Cleaned out from surface to 1943'.

3-23/24-80 Cleaned out 1943' to 2273'.

3-25-80 Cleaned out 2273' to 2880'.

3-26-80 Running tbg w/6-1/2" mill. Cleaned out 2880' to 3013.  
Pulled tbg & 8-1/2" bit.

3-27-80 Ran 2-7/8" tbg & 6-1/2" mill. Went in 7" csg @3100' and  
cleaned out to 3840'.

3-28-80 Cleaned out 3840' to 4248'. Circ & cond. hole.

3-29/31-80 Spotted 65 sxs Cl "H" cmt @4248', 300 sxs @3100'. WOC  
6 hrs. Tagged plug @2875'. Spotted 150 sxs fr. 2875' to 2700'.  
Spotted 150 sx @1766'. Spotted 30 sxs 400' to 300' & 35  
sxs. fr. 100' to surface. Installed marker. Well P & A.

BOP Equip Series 900, 3,000# w/1 set pipe rams & 1 set blind rams, manually operated

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller

TITLE Sr. Engineering Specialist

DATE 5-12-81

OIL & GAS

APPROVED BY W. J. Mueller

TITLE W. J. Mueller

DATE JUN 14 1981

CONDITIONS OF APPROVAL, IF ANY: