


N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



DUPLICATE

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

The Ohio Oil Company

Hobbs, New Mexico

Company or Operator **State Staplin** Well No. **1** in **SE 1/4** of Sec. **30**, T. **17 S**

Lease **35 E**, N. M. R. M., **Vacuum** Field, **East** Lea **West** County.

Well is **660** feet south of the North line and **1980** feet west of the East line of **Sec. 30**

If State land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is _____, Address _____

If Government land the permittee is _____, Address _____

The Lessee is _____, Address _____

Drilling commenced **March 2, 1938** 19 _____ Drilling was completed **April 14, 1938** 19 _____

Name of drilling contractor **Noble Drilling Co**, Address **Tulsa, Oklahoma**

Elevation above sea level at top of casing **3996** feet.

The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from **4450** to **4702** No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
9 5/8	36			505	Reg			
7"	24			4102	Float			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	9 5/8	505	250	Halliburton	10	40
8 1/4	7	4102	700	"	10	40

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **4702** feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing **April 16, 1938** 19 _____

The production of the first **24** hours was **20** barrels of fluid of which **100** % was oil; _____ % emulsion; _____ % water; and _____ % sediment. Gravity, Be _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

Noble Drilling Company

EMPLOYEES

Red Davis Driller **L.P. Cowart** Driller

E. A. McKellips Driller _____ Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **14th**day of **April**, 19 **38**

Notary Public

My Commission expires **March 2, 1941**Hobbs, New Mexico **April 14, 1938**Name **Chas. R. Rasmussen**Position **Supt**Representing **The Ohio Oil Company**Address **Hobbs, New Mexico**

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	18	18	Cellar
18	185	167	Sand & Gravel
185	435	268	Red Beds
435	441	6	Shells-Red rock
441	510	69	Red Beds
510	1180	670	Red Beds-shells
1180	1270	90	Red Beds
1270	1360	90	Red Rock
1360	1431	71	Shells-red rock
1431	1545	114	Red rock
1545	1660	115	Anhydrite
1660	2190	530	anhydrite-salt
2190	2410	220	Salt-anhy-strk of gyp
2410	2508	98	Salt-anhy
2508	2550	42	Anhy
2550	2675	125	Salt-anhy
2675	2692	17	Anhydrite
2692	2715	23	Anhy-strk sand
2715	2787	72	Anhydrite
2787	3213	426	Anhy-gyp
3213	3253	40	Anhy strk lime
3253	3274	21	Anhy-lime
3274	3296	22	
3296	3349	253	Anhy-gyp
3349	3564	15	Anhy-lime
3564	3594	30	Anhy-gyp
3594	3618	24	Anhy-gyp-lime
3618	3635	17	Anhy-lime
3635	3662	27	Anhy-gyp
3662	3688	26	Anhy-gyp-lime
3688	3734	46	Anhy-gyp
3734	3760	26	Anhy-lime-gyp
3760	3806	46	Anhy-gyp
3806	3841	35	Anhy-lime-gyp
3841	3868	27	Anhy-lime
3868	3891	23	Lime-anhy-strk gyp
3891	4007	116	Lime-anhy
4007	4018	11	Lime
4018	4040	22	Lime-anhy
4040	4452	412	Lime
4452	4500	48	Broken lime
4500	4532	32	Lime
4532	4573	41	Grey lime
4573	4702	129	Lime