

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Dallas, Texas

Place

September 19, 1939

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Twin Oil Corporation  
COMPANY OR OPERATOR

State "D"

Well No. 1 in the

LEASE

NE4

of Sec. 30

T.

17S

R.

35E

, N. M. P. M.,

Vacuum

Field,

Lea

County

The dates of this work were as follows: September 13, 1939

Notice of intention to do the work was (~~xxxxxx~~) submitted on Form C-102 on September 1 19 39  
and approval of the proposed plan was (~~xxxxxx~~) obtained. (Cross out incorrect words)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED


A cement plug consisting of 60 sacks of cement was placed from total depth (4700') to 4175' (57' above 5 $\frac{1}{2}$ " casing shoe). The hole was then filled with 100 barrels of drilling mud (Sp.Gr. 1.36). The 5 $\frac{1}{2}$ " casing was shot off at 3190' and 3189' of casing recovered. The hole was then filled with mud and a 10 sack cement plug placed from 1607' (8-5/8" Casing Shoe) to 1576' and a second 10 sack cement plug placed inside the 8-5/8" casing from 30' to surface. A 4" diameter pipe extended 4' above surface level was left to permanently mark this abandoned location. Casing left in hole:

1607' of 8-5/8", 28# Casing

1043' of 5-1/2", 17# Casing

Witnessed by \_\_\_\_\_  
Name

Company



Subscribed and sworn to before me this 19th

day of September, 19 39

Jessie Ross

Notary Public

Dallas County, Texas

My Commission expires June 1, 1941

I hereby swear or affirm that the information given above is true and correct.

Name R. M. Gray

Position Asst. Treasurer

Representing Twin Oil Corporation

Company or Operator

Address Continental Bldg., Dallas, Texas

Remarks:

Roy Warbrough

Name

Oil & Gas Inspector

Title

This work was done by the Maxia Torpedo Company, Wink, Texas  
(foreman Bell) under the supervision of Mr. Lee Bramley, P. O.  
Box 1575, Hobbs, New Mexico.