


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

DUPLICATE

Geo. F. Getty, Inc. (Skelly Oil Co., operator) Hobbs, New Mexico  
Company or Operator Address  
State "N" Well No. 1 in C&W SW of Sec. 33, T. 17S  
R. 35E N. M. P. M. Vacuum Field, Lea County.  
Well is 4620 feet south of the North line and 4620 feet west of the East line of Section 33 -  
If State land the oil and gas lease is No. Assignment No.  
If patented land the owner is Address  
If Government land the permittee is Address  
The Lessee is Geo. F. Getty, Inc. Address Jersey City, N.J.  
Drilling commenced August 7, 1939 Drilling was completed August 7, 1939  
Name of drilling contractor Lee Drilling Company Address Tulsa, Oklahoma  
Elevation above sea level at top of casing 3957 feet.  
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 4220' to 4650' No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.  
No. 1, from to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
13" od	40#	8	LW	21'					
8-5/8"	32#	8	LW	1550' 2"					
5-1/2"	17#	10	SS	4156' 5"					
Tubing									
2"	4.7#	10	SS	4620' 2"					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
15"	13"	21'	25	Dumped (Conductor pipe)		
10 1/2"	8-5/8"	1548'	500	Halliburton (Cement circulated back to cellar)		
6 1/2"	5-1/2"	4140'	400	Halliburton		
Tubing	2"	4598'	Swing			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from top feet to 4650' feet, and from feet to feet  
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing September 8, 1939  
The production of the first 24 hours was 1480 barrels of fluid of which 100 % was oil; %  
emulsion; % water; and % sediment. Gravity, Be  
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas  
Rock pressure, lbs. per sq. in.

EMPLOYEES

A. L. McDow Driller  
C. Dickinson Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 20

day of September 1939

Notary Public  
My Commission expires Dec. 10, 1940

Hobbs, New Mexico-September 20, 1939

Name P. B. Cooper

Position District Foreman

Representing Skelly Oil Co., Operator for  
Geo. F. Getty, Inc.  
Address Hobbs, New Mexico

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	40	40	Caliche & surface sand
40	290	250	Sand & red bed
290	1175	885	Red rock
1175	1235	60	Red bed & red rock
1235	1425	190	Red bed
1425	1485	40	Red bed & red rock
1485	1510	45	Red bed, red rock & sand
1510	1535	25	Red bed
1535	1830	295	Anhydrite
1830	2060	430	Salt, anhydrite & shale
2060	2250	190	Salt & shells
2250	2495	245	Salt
2495	2650	155	Salt, anhydrite & shells
2650	2755	105	Salt & anhydrite
2755	2830	75	Salt, shale & anhydrite
2830	2865	35	Anhydrite
2865	3010	145	Anhydrite & shale
3010	3085	75	Anhydrite
3085	3113	28	Anhydrite & brown lime
3113	3160	47	anhydrite & lime
3160	3205	45	Anhydrite & brown lime
3205	3315	110	Anhydrite
3315	3368	53	Anhydrite & lime
3368	3406	38	Anhydrite
3406	3485	79	Anhydrite & lime
3485	3573	88	Anhydrite
3573	3825	252	Anhydrite, lime & gypsum
3825	3850	25	Lime & gypsum
3850	3875	25	Anhydrite, lime & gypsum
3875	4014	139	Lime & gypsum
4014	4198	184	Lime
4198	4219	21	Gray lime & gypsum
4219	4275	56	Lime
4275	4303	28	Lime & sand
4303	4347	44	Lime & gypsum
4347	4570	223	Lime
4570	4650	80	Lime & sand