

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

HOBBS OFFICE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE

DUPLICATE

The Ohio Oil Company

Hobbs, New Mexico

Company or Operator

Address

State Warr A/c 3

Well No. 2

in SW 1/4 NE 1/4

of Sec. 33

T. 17 S

Lease

R. 35 E

Vacuum

Field,

Lea

County.

Well is 1980 feet south of the North line and 1980 feet west of the East line of Sec. 33

If State land the oil and gas lease is No. B-1713

Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Address

Drilling commenced June 19 19 39 Drilling was completed July 15 19 39

Name of drilling contractor Noble Drilling Company Address Tulsa, Oklahoma

Elevation above sea level at top of casing 3953 feet.

The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 4320 to 4550 No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
9 5/8				800	Reg			
7"	24			4098	Plant			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	9 5/8	500	215	Halliburton	10	40
8 3/4	7	4098	800	Halliburton	10	40

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4550 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing August 1 19 39

The production of the first 24 hours was 54 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity, Ba

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

NOBLE DRILLING COMPANY

EMPLOYEES

Red Davis

Driller

L.P. Cpwart

Driller

S. N. Petest

Driller

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 18

day of July 1939

Notary Public

My Commission expires 10-28-39

Hobbs, New Mexico July 17, 1939

Name

Position

Representing The Ohio Oil Company

Company or Operator

Address Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	19	19	Cellar
19	195	176	Caliche & sand-gravel
195	1210	1015	Red Beds
1210	1530	320	Red rock
1530	1655	125	Anhydrite
1655	2328	673	Salt-anhydrite
2328	2702	374	Salt-shells
2702	2750	48	Anhydrite-streaks of salt
2750	2810	60	Anhydrite-gyp
2810	2887	77	Anhydrite
2887	3040	153	Anhydrite-gyp
3040	3050	10	Brown lime broken
3050	3209	159	Anhydrite-gyp
3209	3260	51	Anhydrite-gyp-brown lime
3260	3459	399	Anhydrite-gyp-streak of lime
3459	3693	234	Anhydrite-gyp-streak of lime
3693	3735	42	Lime-gyp
3735	3761	26	Gyp-anhydrite-lime
3761	3837	76	Lime
3837	3875	38	Lime-anhydrite
3875	4550	675	Lime