#### NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

# MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

#### Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon Well		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		Notice of Intention to Plug Back		Notice of Intention to Set Liner	
Notice of Intention to Squeeze		NOTICE OF INTENTION TO ACIDIZE	x	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	x	Notice of Intention (Other)		Notice of Intention (Other)	

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Roswell, New Mexico

August 4, 1961 (Date) 

erenteta nan

Gentlemen:

Follo	wing is a Notice	of Inter	ntion to do ce	rtain work as de	scribed below at	the		
	Shell	0 <b>11</b> (	Company		State "T"		Well No. 7	I
NE	SE	(Company	or Operator)	-17-9	.14630 -25_F		Vacuum-Abo	(Unit)
	acre Subdivision)	14 of Sec		, T <b>-17-</b> S	, R555-25	,NMPM., .	V & C 2 UN ~1100	Pool

Lea .....County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

## (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

#### Proposed Operation:

- Kill well and pull tubing. 1.
- Perforate 86341 8698! & 8732! 8759! w/2 JSPF. 2.
- Run tubing, set retrievable bridge plug @ 8720', raise tubing, set packer @ 8605', 3. treat perforations 8634' - 8698' w/2000 gallons 15% NE acid.
- Lower bridge plug to 8775' & packer to 8720'. Treat perforations 8732' 8759' 4. w/2000 gallons 15% NE acid.
- 5. Raise packer to 8605'. Swab test perforations 8634' 8759'.
- If warranted treat perforations 8634' 8759' w/10,000 gallons acid petrofrac. 6. Lower bridge plug to 8930' & packer to 8775'. Treat perforations 8790' - 8900' w/10,000 gallons acid petrofrac.
- 7. Swab test all perforations. Pull packer & retrievable bridge plug.

Rerun production string. 8.

Approved 19	Shell Oil Company				
Except as follows:	Company or Operfigural Signed By				
-	By. R. A. LOWERY R. A. LOWERY				
	Position District Exploitation Engineer				
Approved OIL CONSERVATION COMMISSION	Send Communications regarding well to:				
By C C C C C C C C C C C C C C C C C C C	Shell Oil Company				
1 West and the second s	Address Box 1358, Roswell, New Mexico				
Title	Addres DOX 1050, 105WEIL, New Heriot				