

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-03001
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-2519
7. Lease Name or Unit Agreement Name EastVacuum Gb/SA Unit Tract 3467
8. Well No. 027
9. Pool name or Wildcat Vacuum Gb/SA
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3924' GR; 3934' RKB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Phillips Petroleum Company
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762	4. Well Location Unit Letter G : 1980 Feet From The North Line and 1580 Feet From The East Line Section 34 Township 17S Range 35E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.
1. MIRU DDU. NU Class I BOP. GIH w/2-3/8" workstring and on/off tool to 4035' (RBP @4035'). Release RBP and reset @4475'. Circ. well with 9.5 ppg mud-laden fluid.
 2. Spot Plug No. 1 (50 sx cement) 3960'-4475'. This will cover the San Andres, Grayburg, and liner top.
 3. Spot Plug No. 2 (30 sx cement) 2876'-2976'. This will cover the Yates.
 4. Perforate the 7" casing at 1730'. Set packer at 1550'. Squeeze with Plug No. 3 (80 sx. cement) 1599'-1730'. This will cover the salt top and the 9-5/8" shoe. Tag plug.
 5. Perforate and circulate with Plug No. 4 (110 sx. cement) 3'-350' filling the 7" casing and the 9-5/8" x 7" casing full of cement. This will cover the water and surface plug.
 6. Cut off casing 3' below ground level. Install monument marker. Perform reclamation work.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders TITLE Supv., Regulatory Affairs DATE 04-29-94

TYPE OR PRINT NAME L. M. Sanders TELEPHONE NO. (915) 368-1488

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: _____

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR
MAY 03 1994

THE COMMISSION MUST BE NOTIFIED 24
HOURS BEFORE THE BEGINNING OF
OPERATIONS FOR THE C-103

RECEIVED

1931

NOV 1931