

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. <b>30-025-03002</b>
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name <b>EAST VACUUM GB/SA UNIT TRACT 3467</b>
8. Well No. <b>044</b>
9. Pool name or Wildcat <b>VACUUM GB/SA</b>

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	
2. Name of Operator <b>Phillips Petroleum Company</b>	
3. Address of Operator <b>4001 Penbrook Street, Odessa, TX 79762</b>	
4. Well Location Unit Letter <b>H</b> : <b>1650</b> Feet From The <b>NORTH</b> Line and <b>990</b> Feet From The <b>EAST</b> Line Section <b>34</b> Township <b>17-S</b> Range <b>35-E</b> NMPM <b>LEA</b> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) <b>3931, RKB</b>	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. THIS IS NOT A NEW MEXICO RULE 118 WELL.
2. NOTIFY THE NMOCD - HOBBS 24 HRS PRIOR TO START OF PLUGGING OPERATIONS.
3. ALL CEMENT PLUGS TO BE CLASS "C", MIXED AT 14.8 PPG.
4. MIRU SIERRA WELL SERVICE, NU BOPE, COOH W/PKR & TBG.
5. GIH W/WS & TAG CIBP @ 4147', CIRC 5-1/2" CSG W/9.5 PPG MUD LADEN FLUID.
6. SPOT PLUG NO. 1 - 60 SXS CEMENT, 4147'-3740', COVERS SAN ANDRES, GRAYBURG & QUEEN.
7. SPOT PLUG NO. 2 - 25 SXS CEMENT, 2971'-2871'.
8. SQZ 5-1/2" CSG LEAK @ 2148', SET PKR @ 1800',  
SQZ W/ PLUG NO. 3 - 75 SXS CEMENT, 2148'-2048'.
9. CUT 5-1/2" CSG @ 1703', PULL & LAY DOWN.
10. SPOT PLUG NO. 4 - 60 SXS CEMENT, 1703'-1603'.
11. SPOT PLUG NO. 5 - 110 SXS CEMENT, 400'-3', CUT OFF CSG, INSTALL MARKER, CLEAN LOCATION.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Sr. Regulations Analyst DATE 03/15/96

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE MAY 07 1996  
CONDITIONS OF APPROVAL, IF ANY:

