


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

(CORRECTED COPY)

HOBBS OFFICE

AREA 640 ACRES
LOCATE WELL CORRECTLY

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Phillips Petroleum Company

Bartlesville, Oklahoma.

Santa Fe

Company or Operator

Address

Well No. 44 in NE/4 of Sec. 34, T. 17-S

R. 35-E N. M. P. M. Vacuum Field, Lea County.

Well is 990 feet ~~xxx~~ of the North line and 990 feet west of the East line of NE/4 Sec 34

If State land the oil and gas lease is No. B-2519 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Phillips Petroleum Company Address Bartlesville, Oklahoma.

Drilling commenced June 23 19 41 Drilling was completed July 24, 19 41

Name of drilling contractor Phillips Petroleum Co. Address Bartlesville, Oklahoma

Elevation above sea level at top of casing 3923'1" feet. (Ground)

The information given is to be kept confidential until Not confidential 19

OIL SANDS OR ZONES

No. 1, from 4215'0" to 4578'0" No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None logged - drilled with rotary feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8 5/8"OD	32#	10 V	L.W.	1661'10"	Halliburton				Surface String
				(Overall Tally)					
5 1/2"OD	14#	8 rd	SS	4236'5"	Halliburton				Oil String
				(Overall Tally)					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
	8 5/8"	1653'0"	650	Halliburton		
	5 1/2"	4214'11	300	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Did not acidize or shoot.

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 4578 feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing July 25 19 41

The production of the first 10 hours was 145 barrels of fluid of which 100 % was oil; 0 %

emulsion; 0 % water; and 0 % sediment. Gravity, Be. 38.2

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

G. A. Muncy Driller A. E. Bullock Driller

Leonard Chaney Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 4

day of August 19 41

Geo. D. Henshaw
Notary Public

My Commission expires 6-1-43

Odessa, Texas August 4, 1941

Name R. J. Denny

Position District Chief Clerk

Representing Phillips Petroleum Co.
Company or Operator

Address Box 6666, Odessa, Texas

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	254	254	Shale and red bed
254	624	370	Red bed
624	640	16	Lime, hard
640	762	122	Shale and red bed
762	819	57	Shale and red bed
819	870	51	Red bed
870	1280	410	Red bed & shells
1280	1623	343	Red bed & shale
1623	1758	135	Anhydrite
1758	1840	82	Sand
1840	1990	150	Red bed and sand
1990	2140	150	Sand & shale
2140	2210	70	Sand
2210	2549	339	Salt & anhydrite
2549	2625	76	Salt
2625	2860	235	Salt & anhydrite shells
2860	3015	155	Salt & gyp
3015	3084	69	Salt, gyp, anhydrite
3084	3125	41	Gyp & anhydrite
3125	3170	45	Gyp
3170	3190	20	Yates Sand & small amount of gas.
3190	3864	674	Gyp & anhydrite
3864	3921	57	Gyp & Lime
3921	3970	49	Gyp & anhydrite
3970	4061	91	Lime & gyp
4061	4147	86	Lime
4147	4184	37	Lime & sand
4184	4220	36	Lime & anhydrite
4220	4578	358	Lime
	4578		Total depth.