

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Hobbs, New Mexico.

Place

Dec. 19, 1938

RECEIVED
OFFICE

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Standard Oil Co. of Texas. State 6, -34 Well No. 1 in the
COMPANY OR OPERATOR LEASE
N. of S. of Sec. 34, T. 1, R. 33, N. M. P. M.,
Vacuum Field, 1st County

The dates of this work were as follows: Dec. 17 and 18, 1938.

Notice of intention to do the work was (~~XXXXXX~~) submitted on Form C-102 on Verbal 12/17 1938
and approval of the proposed plan was (~~XXXXXX~~) obtained. (Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cemented 9-5/8", 30' casing at 1337' with 115 sacks of 41 lb. Oil well cement. (Caliburton process, Dec. 17, 1938, stood cemented 48 hours. Tested 9-5/8" casing Dec. 18, 1938 with 1000% hydraulic pressure. Let stand 30 minutes- Dropped to 970', Test O.K. Drilled plug at 1521', drilled and cleaned out cement to bottom of well at 1642'. Tested casing and formation with 1100% hydraulic pressure, let stand 30 minutes- dropped to 1000'. Test O.K.

Witnessed by

Ross M. Newman Phillips Pet. Co. Switcher.
Name Company Title

Subscribed and sworn to before me this 20

day of December, 1938

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name J. D. Harris

Position PRODUCTION FOREMAN

Representing Standard Oil Co. of Texas
Company or Operator

Address Box 222 Hobbs, New Mexico.

My Commission expires 10-27-39

Remarks:

R. W. Walker
Name
OIL & GAS INSPECTOR
Title