

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

| | | | |
|--|---|--|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | X | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | | |

September 29, 1949

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Standard Oil Co of Texas State #6 Well No. 3 in the _____

SW $\frac{1}{4}$ of SW $\frac{1}{4}$ Company or Operator 34 Lease 17-5 35-E
Vacuum of Sec. 34, T. 17-S, R. 35-E, N. M. P. M.,
Field, Lea County.

The dates of this work were as follows: September 27, 1949

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on Sep 29, 1949
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.) Verbal 9-23-49

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cemented 9 5/8" 36# casing at 1730 with 750 sacks of Longhorn 2% gel cement. Halliburton one plug method September 25, 1949. Stood cemented 50 hours. Tested 9 5/8" casing with 1000psi hydraulic pressure. In 30 minutes pressure dropped to 940 psi. Drilled cement plug and tested with 1000 psi hydraulic pressure. In 30 minutes pressure dropped to 920 psi.

Witnessed by _____

Name

Company

Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

29 day of Sept. 1949

Name John M. McMahan

Position Petroleum Engineer

Representing Standard Oil Co of Texas

Notary Public

Company or Operator

My commission expires 10/24/53

Address Box AA, Hobbs, New Mexico.

Remarks:

Roy Garbraugh

Name

Title