OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below

	or rebo	rt by checking b	elow.		
REPORT ON BEGINNING DRILLING OPERA-		REPORT ON	REPAIRING WELI	<u> </u>	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON	PULLING OR OTH	TERWISE	-
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	x	 	DEEPENING WEI	LL	-
REPORT ON RESULT OF PLUGGING OF WELL					
Decembe	er 1,	1949	Hobbs, New	Werton	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO Gentlemen:		Date		Place	
Following is a report on the work done and the results Standard Oll CO Of TOXAS S/2 Company or Operator 24	ts obtaine Sta	d under the hea	ding noted above at	the	
		100000	72 5 73		
oi Sec	ea, T		, R	, N.	M. P. M.,
The dates of this work were as follows: December	r 1,	1949			County.
Notice of intention to do the work was () s	anhmitte.	1 T- C 10	Morrowhen	00	
and approval of the proposed plan was (was hot) of	submitte	on Form C-10	2 on ROV GINUEL	29,	19 49
DETAILED ACCOUNTS OF THE	obtained.	(Cross out inco	rrect words.)		
9 5/8" casing was landed and The casing was tested for water	ORK DO	NE AND RESI	JLTS OBTAINED	40	
				r 29, .	1949.
48 hours cement time. Testing	- 0 MAG	-OII Decell	tber I, 1949,	follo	wing
1. After locating the amount	010060	uro was a	s follows:		
1. After locating the cemer of 1000 psi was applied	nt bri	ig at 1597	'' a hydrauli	c pres	su re
of 1000 psi was applied. 2. The cement plug was dril	· Ine	re was no	pressure lo	ss in	30 mins
2. The cement plug was dril of 1000 psi was applied	rred t	o 1672.	A hydraulic	oressu	18
	• The	ere was a	pressure los	s of 25	nei
					par
John M. McMahan	Standa	rd 0il Co	of Texas	Pet Eng	موين
vionesseu by				a o a mare	54
Name		Compar	пу	Tit	le
Subscribed and sworn before me this	I he	ereby swear or	affirm that the infor	mation give	en above
day of		rue ping contect.	that the infor	•	
19.40	7. Nan		1. Mc malian		
Millanahan	Posi	tion Petro	leum Enginee	r	
Notary Public	-	Star	dard Oil Co	of Tex	as
		(Company or Operator		
My commission expires 18/24/V3	Add	ress Box AA	, Hobbs, New	Mexico	
emarks:			Roe was	diase	sil.
			AT	Nam	3

Title