

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.		5a. Indicate Type of Lease State ☒ Fee ☐
6. State Oil & Gas Lease No. B 1845		7. Unit Agreement Name Vacuum Abo Unit
8. Farm or Lease Name Bury 2 Vacuum Abo Unit Tract 10		
9. Well No. 5		10. Field and Pool, or Wildcat Vacuum Abo Reef
11. Elevation (Show whether DF, RT, GR, etc.) 3923' RKB		
12. County Lea		

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐ IMPROVISE ABANDON ☐ PLUG OR ALTER CASING ☐ OTHER ☐	PLUS AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐	REMEDIAL WORK ☒ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☐	ALTERING CASING ☐ PLUS AND ABANDONMENT ☐ OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

-2-75: MI Johnson unit, pld rods and tbq.

-3-75: Plugged back in Abo formation f/8760' to 8724' w/700# Hydromite.

-4-75: Western perforated Abo formation thru csg w/2 jet shots/ft from 8694-8720', total 26', 52 holes. Set 2-3/8" tbq at 8600' w/Baker R pkr on bottom. Swbd 4 hrs, 25 BO, 2 BSW.

-5-75: Runco treated down 2-3/8" tbq thru Abo perfs 8694-8720' w/2500 gals 28% HCL NE acid w/ ball sealers. Flushed w/37 BW. Max press 1700#, min 900#, ISDP 0#. AIR 1 BPM. Down 5 hrs to repair unit.

-6-75: Swbd 9 hrs, 57 BO, 84 BLW.

-7-75: SD 24 hrs.

-8-75: Pld 2-3/8" tbq & pkr. Set 2-3/8" tbq at 8690' w/anchor-catcher on bottom. Set 2"x1 1/4"x 20' pmp at 8689. Released unit. P/14 hrs—no gauge.

-9-75: P/24 hrs, 100 BO, 16 BSW.

-10-75: P/24 hrs, 33 BO, 48 BSW.

-11-75: P/24 hrs, 18 BO, 38 BSW.

-12-75: P/24 hrs, 20 BO, 40 BSW.

-13-75: P/24 hrs, 25 BO, 35 BSW.

-14-75: P/24 hrs, 30 BO, 40 BSW, GOR 176/1, perfs 8694-8720'. Restored to production.

Equipment: Series 900, 3000# WP, double w/one set blind rams, one set pipe rams. Manually operated.

hereby certify that the information above is true and complete to the best of my knowledge and belief.

[Signature] W.J. Mueller TITLE Engineering Advisor DATE 9-15-75

VED BY *[Signature]* John R. *[Signature]* TITLE DATE SEP 22 1975

ITIONS OF APPROVAL, IF ANY