

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico

(Place)

October 4, 1961

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Cities Service Petroleum Company State BJ Well No. 4 in M  
(Company or Operator)  
SW 1/4 SW 1/4 of Sec. 35, T. 17S, R. 35-E, NMPM, East Vacuum Abo Pool  
(40-acre Subdivision) Lea County.

## FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

T.D. 9233' Dolomite. This well was spudded at 12:00 noon August 23, 1961. Ran 337.71 of 13-3/8" OD 48# 8R H-40 SS casing, set @ 353.51'. Cement circulated. Ran 3534.62 of 8-5/8" OD 32 & 24# J-55 SS casing, set @ 3549.72. Cemented with 1682 sacks 50-50 dia-mix plus 350 sacks neat cement. The well was logged and tested by swabbing with Lynes straddle packers set at 8510'-8575.5'. The tubing was swabbed dry. Acidized with 2000 gallon mud acid and swabbed for 9 hours. Recovered 5.5 barrels of oil and 1.85 bbls. water. Since the well is non-commercial, it is proposed to plug and abandon as follows: (1) load hole with mud laden fluid; (2) spot 50 sack plug 9233'-9059'; (3) spot 50 sack plug 8400'-8226'; (4) spot 50 sack plug 6650'-6476'; (5) spot 50 sack plug 5650'-5476'; (6) spot 50 sack plug 4874'-4700'; (7) spot 50 sack plug 3704'-3530'; (8) spot 10 sack plug at surface with 4" marker extending 4' above the surface. The location will be cleared of all debris, pits filled and location leveled in a workman-like manner.

Approved Verbal approval received.  
Except as follows: \_\_\_\_\_, 19\_\_\_\_

Approved  
OIL CONSERVATION COMMISSION

By \_\_\_\_\_  
Title \_\_\_\_\_

Cities Service Petroleum Company

Company or Operator

By \_\_\_\_\_

Position District Superintendent

Send Communications regarding well to:

Name George M. Geyer

Address Box 97, Hobbs, New Mexico