

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

4-9-53
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Phillips Petroleum Company Santa Fe Well No. 47 in C
(Company or Operator) (Unit)
NW 1/4 NW 1/4 of Sec. 35, T. 17S, R. 35E, NMPM., Vacuum Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was shut down during January, 1949, because its daily production had declined to twenty barrels of water and no oil. Propose to run Lane Wells Radioactivity Survey. Plug back to 4500' with Pea gravel capped with Hydramite. Hydrafrac open hole, Grayburg Formation, with 3000 gallons and test. If Grayburg cannot be successfully recompleted, plug back to Yates Formation perforate, acidize and test. If non-commercial plug and abandon, by loading hole with heavy mud, shoot 5-1/2" casing at approximately 2300' and recover; spot 10 sack cement plug at point where 5-1/2" shot off and 10 sack cement at bottom of 8-5/8" casing which is set at 1708'. The 8-5/8" casing is circulated with cement and no attempt to be made to recover. Set pipe marker in cement at surface.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By Ray Yarbrough

Title.....

Phillips Petroleum Company
Company or Operator

By M. G. Croston

Position District Chief Clerk
Send Communications regarding well to:

Name M. G. Croston

Address Box 2105 - Hobbs, New Mexico