											: • • •	in Brank	س					-	
NUMBER OF COPIE										ġ.	Novine 1 Press	/1 <b>/32</b>	. ; <del></del>	1	1	1	1	Ī	1
OIS	TRIBUTIO	IN I											and the second	· · · · ·				+	┝
FILE								ONSER			للالل ه	10.	. HI	6	29				
U.S.G.S				NEW	MEA		IL C	UNSER	VAIR	UNICA	UNEMAL	NIO.							
TRANSPORTER	OIL					S	anita 🛛	Fc, New	/ Mexi	<b>C</b> 3				$\vdash$		-+-		+	
PROBATION OFFIC	GAS																ļ		
OPERATOR													-						
later	than t	strict Off	s after o	omplet	ion of v	Commissi vell. Foll	ion, to low in	tructions	Form C in Rul	-101 v les and	Regulat	ions 🚦				0			
		mission. S		-													ACRES		
•••••		Earl G	<u>Colt</u>									Cabo	t Ca	rber	Sta	te	*****	********	
Well No																			
WCH 140																			
Well is		-		-															
of Section																			
Drilling C																			
Name of 1			-																
; Address	-	-																	
Elevation	above	sea level a	t Top of	Tubin	g Head														
							OIL S	ANDS O	R ZOP	TES									
No. 1, from	m	4950		to	)	4952			No. 4, f	rom		•••••		ta	D	<b></b>			******
No. 2, from	m	4954		ta		<b>496</b> 2	) {	P	No. 5, f:	rom				to	)	•••••		••••••	•••••
No. 3, from	m			to			I	1	No. 6, f	rom				ta	) <i></i>	•••••			
						IMP	ORT	LNT WA	TER S	ANDS									
Include da	ata on	rate of w	ater inflo	w and	elevation														
No. 1, from	m	letary.	Hole			to						.feet.					•••••		
No. 2, fro	m					to			•••••			.feet.				•••••			•••••
No. 3, from	m					to					•••••••••••	.feet.			•••••	••••••	•••••••••		••••••
No. 4, froi	m					to						feet.							

	CASING BECORD						
SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	Used	165	Gnide			Surface
5 1/2	15.5	New	5041	Guide		4950-52 54-62	Production
/-						64-66	
_							

MUDDING AND CEMENTING RECORD						
IZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METROD USED	MUD Gravity	AMOUNT OF MUD USED
11	8 5/8	165	100	P&P		· · · · · · · · · · · · · · · · · · ·
7 7/	8 5 1/2	5041	150	P&P		

## **BECORD OF PRODUCTION AND STIMULATION**

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Saudfrac 20,000 gal refined eil, 31,000# 20-40 Sand and 750 gals 15% NE acid. Avg. rate 25.8 BOPM. Avg. treating pressure 3,300#.

\_\_\_\_\_

Result of Production Stimulation.....

## RECORD OF DRILL-STEM AND SPECIAL TIMES

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

			0		TOOLS US 5.044	ED			
Rotary tools were used fromfeet			t to	<b>V; V11</b>	feet, and from		feet to	fact	
Cable tools were used fromfeet to			•••••••••••••••••••••••••••••••••••••••	feet, and from			fret		
			ne 7,		PRODUCT				
Pu	t to Produci	ing			19				
	IT WETT.	The meduation			76			80	•
0.		The production	<b>0</b>	nours was	20	barrels	of li	quid of which	was
		was oil;	25	s emulsion;	;	% water; an		% wa	s sediment. A.P.I.
			JJ 81 14						
~								`	
GA	AS WELL:	The production	during the first 24	hours was	•••••••••••••••••••••••••••••••••••••••	M.C.F. plus	•••••		barrels of
		liquid Hydroca	rbon. Shut in Pressui	тс	ibs.				
L	ngth of Tin	a Shut in							
	PLEASE	INDICATE BE			IN CONFO	RMANCE WITH GI	EOG	RAPHICAL SECTION	OF STATE):
		1768	Southeastern New	Mexico				Northwestern Ne	w Mexico
Т.				r. Devoni	an		Т.	Ojo Alamo	
Т.				D. Siluria	n		Т.	Kirtland-Fruitland	
B.				C. Monto	ya,.	·····	Т.	Farmington	
Т.				C. Simpso	n		Т.	Pictured Cliffs	
Т.	7 Rivers	.4528		C. McKee	* •	3	Т.	Menefee	
Т.	Queen			. Ellenbu	irger	••••••	T.	Point Lookout	
T.			-	. Gr. Wa	ash		Т.	Mancos	•••••••
T'.	San Andre	s	Т	. Granite			Ť.	Dakota	
T.	Glorieta		T		•••••		Т.	Morrison	
т.	Drinkard		т				Т.	Penn	
Т.	Tubbs		T						
Т.	Abo		T		•••••••			•••••••••••••••••••••••••••••••••••••••	
Т.	Penn		r	• • • • • • • • • • • • • • • • • • • •					
Т.	Miss		т	• • • • • • • • • • • • • • • • • • • •					

## FORMATION RECORD

From	То	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
3140 3325	1768 1962 3140 3325 4528 5044	1768 194 1178 185 1203 516	Red Sand & Shale Anhydrite Salt & Anhydrite Dolemite & Anhydrite Anjydrite, Dolomite & Sand Sand, Anhydrite & Dole- mite				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

.

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

	June 8, 1961
EARL G. COLTON	Box 2076, Hobbs, New Mexico (Date)
Company or Operator	Address.
Name	Posicial of Title. Agent Aue Womple