

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE D.C.C.

MISCELLANEOUS NOTICES **Mar 9 9 02 AM '64**

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	Convert to Dual Injection Well

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico

February 28, 1964

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company East Pearl-Queen Unit

Well No. 21-36 in P

(Company or Operator)

SE $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 21, T. 19 S, R. 35 E, NMPM., Pearl-Queen (Unit)

(40-acre Subdivision)

Pool

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull tubing and packer.
2. Perforate Zones IIA at 4772-4790' with two JSPF;
IIIA at 4818-4824' and 4830-4833' with two JSPF;
IIIB at 4838-4842' with two JSPF;
IV at 4849-4851' with two JSPF
3. Run tubing with packer and set at approximately 4725' and test for communication.
4. Set packer @ approximately 4700' between Zones I and IIA perforations.
5. Run seal assembly on 2" plastic coated tubing with dual packer spaced to set at 4610' with 1 $\frac{1}{2}$ " tubing above dual packer.
6. Run 1-1/2" short string with seal assembly and set dual packer.
7. Hook up plastic coated well head and start injecting.

NMOCC Order No. R-2538

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....

Shell Oil Company

Original Signed By
By R. A. Lowery R. A. LOWERY
Company or OperatorPosition.....
District Exploitation Engineer

Send Communications regarding well to:

Name.....
Shell Oil Company
Address.....
Box 1858 Roswell, New Mexico