

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES MAR 9 9 02 AM '64

submitted to the school on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Convert to	X	NOTICE OF INTENTION (OTHER)	

Dual Injection Well

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico

February 28, 1964

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company

East Pearl-Queen Unit

Well No. ~~21-14~~ // in N

(Company or Operator)

SE

1/4

SW

1/4 of Sec.

21

T. 19-S

Lease

35-E

NMPM,

Pearl-Queen

(Unit)

Pool

(40-acre Subdivision)

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Clean out to PBTD and test for communication between Zones I and IIIA.
2. If Zones I and IIIA are in communication, set cement retainer between Zones I and IIIA perforations, squeeze through Zone IIIA perforations, drill out cement and retainer and re-perforate.
3. Set permanent packer at approximately 4800' between Zones I and IIIA perfs.
4. Run 2" plastic coated tubing with seal assembly and dual packer spaced to set at 4710'.
5. Run 1" plastic coated tubing with seal assembly and set dual packer.
6. Load annulus with inhibited water.
7. Hook up plastic coat d well head and start injecting into upper zone at rate of 73 B/D and lower zone at rate of 64 B/D.

NMOCC Order No. R-2538

Approved....., 19.....
Except as follows:

Shell Oil Company

Company or Operator

By R. A. Lowery Original Signed By

R. A. LOWERY

Position District Exploitation Engineer

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Name Shell Oil Company

Address Box 1858 Roswell, New Mexico