Form C-102		(D)~	
NEW EXICO OIL CONS	ERVATION COMI SION	11 Dipan	
Santa Fe, N	ew Mexico	IT SED	21/2
MISCELLANE	OUS NOTICES		Th)
Submit this notice in triplicate to the Oil Conservation C to begin. A copy will be returned to the sender on which sidered advisable, or the rejection by the Commission or be followed, and work should not begin until approval i Regulations of the Commission.	agent of the plan submitted T	with any modification	tied is s con- s con- s con- s con- s con- s con- t con- s con- con- con- con- con- con- con- con-
NOTICE OF INTENTION TO TEST CASING	NOTICE OF INTENTION TO	SHOOT OR	
SHUT-OFF	CHEMICALLY TREAT WELL		
NOTICE OF INTENTION TO CHANCE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING		
NOTICE OF INTENTION TO REPAIR WELL			
NOTICE OF INTENTION TO DEEREN WELL	NOTICE OF INTENTION T	O PLUG WELL	<u> </u>
Hot	1	ber 19-1941	
\	Place	Date	
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico		Date	
Gentlemen:			
Following is a notice of intention to do certain work as de	scribed below at the		
	Well No	<b>C–SW</b> 25	NŻ
of SecT. 19 S R. 35 E Lease	Wildcat		
or sec T R,	N. WI. P. M.,		Field,
County.			
County,			
FULL DETAILS OF PRO	POSED PLAN OF WORK		
FULL DETAILS OF PRO FOLLOW INSTRUCTIONS IN THE RULES of propose to set cement plug of 15 sax bel aving filled hole with mud below this poin	AND REGULATIONS OF THE ow base of salt at app.	roximately 3200	16
FULL DETAILS OF PRO	AND REGULATIONS OF THE ow base of salt at app t. We will then set a t with hole full of he ill hole to surface with at 1634 feet in hole	roximately 3200 cement plug of avy mid between th heavy mid les will then set	15 sax plug
FULL DETAILS OF PRO FOLLOW INSTRUCTIONS IN THE RULES . We propose to set cement plug of 15 sax bel- having filled hole with mud below this point in top of the Rustler Anhydrite at 1750 feet at 3200 feet and 1750 feet. We will then f b-1/4" casing which is cemented with 500 sa bips them cement plug at surface with same in 10	AND REGULATIONS OF THE ow base of salt at app t. We will then set a t with hole full of he ill hole to surface with at 1634 feet in hole	roximately 3200 cement plug of avy mid between th heavy mid lea . Will then set surface.	15 sax plug
FULL DETAILS OF PROT FOLLOW INSTRUCTIONS IN THE RULES. We propose to set cement plug of 15 sax believing filled hole with mud below this point in top of the Rustler Anhydrite at 1750 feet \$3200 feet and 1750 feet. We will then f -1/4" casing which is cemented with 500 satisfies them cement plug at surface with same in	AND REGULATIONS OF THE ow base of salt at app t. We will then set a t with hole full of he ill hole to surface wir x at 1634 feet in hole axtending 6 feet above Uscan Drlg. Co. Company or Oper By Kugh We	roximately 3200 cement plug of avy mid between th heavy mid lea . Will then set surface.	15 sax plug
FULL DETAILS OF PRO FOLLOW INSTRUCTIONS IN THE RULES	AND REGULATIONS OF THE ow base of salt at app t. We will then set a t with hole full of he ill hole to surface wit x at 1634 feet in hole axtending 6 feet above	roximately 3200 cement plug of avy mid between th heavy mid lea . Will then set surface.	15 sax plug
FULL DETAILS OF PROT FOLLOW INSTRUCTIONS IN THE RULES. We propose to set cement plug of 15 sax believing filled hole with mud below this point in top of the Rustler Anhydrite at 1750 feet \$3200 feet and 1750 feet. We will then f -1/4" casing which is cemented with 500 satisfies them cement plug at surface with same in	AND REGULATIONS OF THE ow base of salt at app t. We will then set a t with hole full of he ill hole to surface win x at 1634 feet in hole axtending 6 feet above Uscan Drlg. Co. Company or Oper By Mugh We Position Toolpusher	roximately 3200 cement plug of avy mid between th heavy mid lea . Will then set surface.	15 sax plug



аналан 1997 - Алар Алар Алар (1997) 1997 - Деректер Дар Алар (1997) • • .