

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE MISCELLANEOUS REPORTS ON WELLS

SEP 8 1947
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

September 2, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation **Henry S. Record** Well No. **2** in the _____
 Company or Operator Lease

SE 1/4 NE 1/4 of Sec. **25**, T. **19S**, R. **35E**, N. M. P. M.,
Wildcat Field, **Lea** County.

The dates of this work were as follows: **August 30, 31, September 1, 1947**

Notice of intention to do the work was ~~(crossed out)~~ submitted on Form C-102 on **August 30,** 19**47**
 and approval of the proposed plan was ~~(crossed out)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

4534' Total Depth, Lins. 4443' bottom of 15" hole. Ran 110 joints of 11-3/4" OD, 47#, J-55, R-3, 8-RT, Reg. TB, National Tube SS Casing and set at 4443'. Cemented with 1000 sacks of El Toro Regular Cement 3% Howeogel and 500 sacks of Trinity Slo-Set Cement and plug pumped to 4360' at 9:10PM, August 1, 1947. Final pressure 700#. Ran 5 sacks Aquagel ahead of cement.

Witnessed by **D.F. Furse** **Amerada Petroleum Corporation** **Foreman**
 Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

2nd. day of **September**, 19**47**

Name *Don Topp*Position **Asst. Dist. Supt.**

Representing **Amerada Petroleum Corporation**
 Company or Operator

My commission expires **My Commission Expires May 9, 1948**

Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

SEP 8 1947

Roy Yankrough
 OIL & Gas Inspector

Title

Handwritten signature or text at the bottom left corner.