

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILL	
USGS	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PERFORATION OFFICE	
OPERATOR	

(Form C-102)  
(Revised 7/1/82)

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HQB38 DECE 2. C. C.

## MISCELLANEOUS NOTICES

MAR 9 9 03 AM '64

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be required to the school on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	Convert To Injection Well

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Roswell, New Mexico  
(Place)

March 4, 1964  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Shell Oil Company East Pearl-Queen Unit Well No. 2726 38 in P  
(Company or Operator) (Unit)  
SE 1/4 SE 1/4 of Sec. 27, T. 19 S, R. 35 E, NMPM, Pearl-Queen Pool  
(40-acre Subdivision)  
Lea County.

### FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull tubing and packer.
2. Run GR/CCL log from casing shoe to 4550' and adjust to Schlumberger GR/Sonic log.
3. Set cement retainer at 4896' in 5 1/2" casing and squeeze open hole with cement.
4. Perforate Zone IIIA at 4872-4875' with four JSPF.
5. Run 2 1/2" tubing with Baker Model R dual-grip packer and set at 4850'. Treat perforations below packer with 500 gallons 15% FE NEA.
6. Hook up well head and start injecting.

NMOCC Order No. R-2538

Approved..... 19.....  
Except as follows:

Shell Oil Company

Company or Operator

By..... R. A. Lowery Original Signed By

Position..... District Exploitation Engineer

Send Communications regarding well to:

Shell Oil Company

Name.....

Box 1858 Roswell, New Mexico

Address.....

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....