NUMBER OF COPIE	IS RECEIVED			
DISTRIBUTION				
SANTA FE				
FILE		1		
U.S.G.S.		· · · · · · · · ·		
LAND OFFICE		11		
TRANSPORTER	OIL	1		
	GAS			
PRORATION OFFIC	с	I		
OPERATOR		1		

## EW MEXICO OIL CONSERVATION COMMISSION 0. C. C. Santa Fe, New Mexico HOBBS OF THE 0. C. C. MISCELLANEOUS NOTICES 9 02 AM '64

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Notice by Checking Below

Notice of Intention	NOTICE OF INTENTION TO	Notice of Intention
to Change Plans	TEMPORARILY ABANDON WELL	to Drill Deeper
NOTICE OF INTENTION	Notice of Intention	Notice of Intention
TO PLUG WELL	to Plug Back	to Set Liner
Notice of Intention	Notice of Intention	Notice of Intention
to Squeeze	to Acidize	to Shoot (Nitro)
Notice of Intention to Gun Perforate	NOTICE OF INTENTION (OTHER)	Notice of Intention (OTHER) Convert To Dual Injection Well

OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

Roswell, New Mexico (Place) (Date)

March 3, 1964

Gentlemen:

Follow	wing is a Noti	ce of Intention to	do certain work	as described	below at th	he		••••••
	Shell 011	Company	East Pear	1-Que en	Unit		Well No 26 in	F
SE	NW	(Company or Oper 27	ator) 19		35"E	.N <b>MPM</b>	Pearl-Queen	(Unit) Pool
Lea	acre Subdivision)	,.	,	·····,·		,- ·,		

.....County.

## FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

- 1. Pull rods, pump and tubing.
- 2. Clean out to PBTD.
- 3. Run tubing with packer and set packer between Zone I and Zone IIA perforations and test for communication between Zone I and lower zones.
- 4. Install permanent packer at 4750'.
- Run 2" plastic coated tubing with seal assembly and special dual packer spaced 5. to set at 4660'. Set packer - 2" tubing from dual packer short string connection to permanent packer.
- 6. Run 1" plastic coated tubing with seal assembly.
- Hook up well head and start injecting. 7.

NMOCC Order No. R-2538

Approved, 19	Shell Oil Company
Except as follows:	Company or Operator iginal Signed By R. A. LOWERY B. A. LOWERY
	District Exploitation Engineer
Approved OIL CONSERVATION COMMISSION	Send Communications regarding well to:
By	Shell Oil Company
Tide.	Box 1858 Roswell, New Mexico