

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

DUPLICATE

Submit this notice in triplicate to the Oil Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commissioner or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

| | | |
|---|-------------------------------------|--|
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO SHUT-OFF OF CHEMICALLY TREAT WELL |
| NOTICE OF INTENTION TO CHANGE PLANS | <input type="checkbox"/> | NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING |
| NOTICE OF INTENTION TO REPAIR WELL | <input type="checkbox"/> | |
| NOTICE OF INTENTION TO DEEPEN WELL | <input type="checkbox"/> | NOTICE OF INTENTION TO PLUG WELL |

NOV 14 1939
RECEIVED
HOBBBS OFFICE

Monument, New Mexico.

November 6, 1939.

Place

Date

OIL CONSERVATION COMMISSION,

Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Amerada Petroleum Corporation State LA Well No. 5 in C of SE NE $\frac{1}{4}$
Company or Operator Lease
of Sec. 1, T. 17S, R. 36E, N. M. P. M., South Lovington Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

This well has been drilled to a total depth of 3096'. The formation is anhydrite. 8 5/8" seamless casing has been set @ 3091' and cemented with 200 sacks of El Toro Common and 50 sacks of El Toro special cement. The plug was pumped to 3029' @ 10:20 a.m. 11/6/39.

The well will be allowed to stand undisturbed for a period of 72 hours. Pump pressure of 1200# will then be applied to the pipe and fittings, the valves closed, and the pressure within observed for a period of 30 minutes. If there is no drop in pressure, the cement plug will then be drilled and the same test again applied. If there is no drop in pressure, drilling will be resumed.

Approved

except as follows:

NOV 14 1939

, 19

AMERADA PETROLEUM CORPORATION

Company or Operator

By

Position

Superintendent

Send communications regarding well to

Name

J. E. Low

Address

Monument, New Mexico.

OIL CONSERVATION COMMISSION,

By

Title

OIL & GAS INSPECTOR