

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF EXPLORATION	
CITY SECTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-2359	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Texaco Producing Inc.

Address of Operator

P. O. Box 728, hobbs, NM 88240

Location of Well

UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM
THE East LINE, SECTION 1 TOWNSHIP 17S RANGE 36E NMPM.

7. Unit Agreement Name

Loyington San Andres Unit

8. Farm or Lease Name

9. Well No.

33

10. Field and Pool, or Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)

3836' DF

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☒	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
WELL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 1) MIRU 07/14/86.
- 2) Clean out to PBTD @ 4775' w/4 3/4" bit. (Tag fill @ 4612').
- 3) Run GR-CNL-CCL- Caliper 4775'-2750' Run GR-CBL 4591-4400'.
- 4) Fill OH 4775'-4591' w/sand. Set CIBP @ 4585'.
- 5) Perf Grayburg w/2JSPI @ 4481, 4509, 18, 35, 43, 46, 52, 56, 61, 66, 69 (Total 22 holes).
- 6) Acidize perfs 4481-4569' w/5000 gal gelled 15% NEFE and 1 drum Surflo H-35 Scale Inhibitor and 44 ball sealers. Ball out. Air 5BPM, Ave Press. 3600, ISIP 3000, 15 min. 2800.
- 7) Pump approx. 17 days. Ave. 30 BOPD, 20 BWPD from Grayburg.
- 8) MIRU. Drill out CIBP and clean out to PBTD @ 4775'.
- 9) Set pkr @ 4577'. Acidize San Andres 4591-4775' w/5000 gal gelled 15% NEFE and 1 drum Surflo H-35 scale inhibitor in 3 stages w/500# rocksalt in 10 bbls gelled brine between stages. Communicated w/Grayburg perfs w/5 bbls acid pumped. Little block action. Air 1.7 BPM, Ave press. 3000#, ISIP 2800#, 15 min 1600#.
- 10) RD. Place on production 08/10/86.
- 11) Before Wo 1 BOPD, 1 BWPD. After Grayburg 30 BOPD, 20 BWPD, San Andres 12 BOPD, 30 BWPD.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE District Admin. Supervisor DATE 09/05/86

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: