


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL



Title

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports to be the comparison, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important approximations, even though the work was witnessed by an agent of the commission. Because on miner operations need not operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

OPERATIONS		l)				
EPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	,	REPORT ON I	PULLING OR G CASING	OTHERW	ISE	
EPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON I				
EPORT ON RESULT OF PLUGGING OF WELL						
Monu	ment,	New Mexico,	Jan	uary 1,	1940.	
OIL CONSERVATION COMMISSION,		Place			Date	
Santa Fe, New Mexico.						
Gentlemen:						
Company or Operator Work of NE 1 of Sec.	esults of	btained under the S tate LA	e heading not	ed above at 6 No	t thein	the
Company or Operator	1	Lease 17s		36 e		
of Sec.	<u>-</u> T.,	, T	, R.		, N. M	. Р. М.,
South Lovington Field,						
The dates of this work were as follows: Water (************************************				00 70		
Notice of intention to do the work was (************************************	submitte	ed on Form C-10	2 on 12	-28-39		. 19
nd approval of the proposed plan was (was not)						
DETAILED ACCOUNT OF Volume This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied	of 45 s of E 5'. to th	95'. 5 1/2" Il Toro commo	OD 17# sen cement	eamless of and 50 s	casing had sacks of the	Quicks osed s
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressures within observed for a percement plug was then drilled and the Drilling was resumed December 30, 1	of 45 s of E 5. to the riod one sam	95'. 5 1/2" Il Toro commo e pipe and o f 30 minutes se test again	OD 17# seen connections. There was applied	amless of and 50 some the viras no do without	casing had sacks of over valves clumps rop in pr drop in	duicks osed s essure pressu
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressures within observed for a percement plug was then drilled and the Drilling was resumed December 30, I	of 45 s of E 5. to the riod one sam	95'. 5 1/2" Il Toro commo e pipe and o f 30 minutes se test again	OD 17# seen connections. There was applied	amless of and 50 some the viras no do without	casing had sacks of over valves clumps rop in pr drop in	duicks osed s essure pressu
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressurem within observed for a percement plug was then drilled and the Drilling was resumed December 30, I witnessed by Roy Campbell	of 45 s of E 5'. to th riod o ne sam	95'. 5 1/2" Il Toro commo e pipe and of f 30 minutes te test again Noble Dri	OD 17# seen connections. There is applied	eamless of and 50 s the vas no do without	casing had acks of valves close of the contract of the contrac	uicks osed s essure pressu
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressurew within observed for a percement plug was then drilled and the Drilling was resumed December 30, I witnessed by Roy Campbell	of 45 s of E 5'. to th riod o ne sam	95'. 5 1/2" Il Toro commo e pipe and of f 30 minutes te test again Noble Dri	on cement connection. There is applied	amless of and 50 sets the vas no do without	casing had acks of valves close of the contract of the contrac	uicks osed s essure pressu
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressurew within observed for a percement plug was then drilled and the Drilling was resumed December 30, I witnessed by Roy Campbell Name	of 45 s of E 5'. to th riod o ne sam	95'. 5 1/2" Il Toro commo e pipe and of f 30 minutes te test again Noble Dri	OD 17# seen connections. There is applied	amless of and 50 sets the vas no do without	casing had acks of valves close of the contract of the contrac	uicks osed s essure pressu
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressurex within observed for a per cement plug was then drilled and the Drilling was resumed December 30, I Witnessed by Roy Campbell Name Subscribed and sworn to before me this 2nd day of January	of 45 s of E s. to the riod one sam	95'. 5 1/2" Il Toro commo e pipe and of f 30 minutes test agair Noble Dri Company I hereby swear is true and cor	on cement connection. There is applied connection or affirm the rect.	amless of and 50 sets the visas no di without	casing had acks of valves close of the contract of the contrac	uicks osed s essure pressu
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressurew within observed for a percement plug was then drilled and the Drilling was resumed December 30, I witnessed by Roy Campbell Name	of 45 s of E s. to the riod one sam	95'. 5 1/2" Il Toro commo e pipe and of f 30 minutes test agair Noble Dri Company I hereby swear is true and cor Name Position	on coment connections. There is applied allin Con or affirm the rect.	amless of and 50 s the ras no do without mpany at the information of the condent	casing had acks of valves close of the contract of the contrac	usher
This well had been drilled to a TD @ 4589' and cemented with 150 Sacks cement. The plug was pumped to 4523 Pump pressure of 1200# was applied pressurex within observed for a per cement plug was then drilled and the Drilling was resumed December 30, I Witnessed by Roy Campbell Name Subscribed and sworn to before me this 2nd day of January	of 45 s of E s. to the riod one sam	95'. 5 1/2" Il Toro commo e pipe and of f 30 minutes test agair Noble Dri Company I hereby swear is true and cor	on cement connections. There is applied allin Con or affirm the rect. Supering Amerada	amless of and 50 sets the vas no do without mpany at the information of the content of the conte	tasing had sacks of walves close of property of the results of the control of the	usher