

**DUPLICATE**

NEW MEXICO OIL CONSERVATION CO. COMMISSION

Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

**RECEIVED**  
JAN 2 - 1940  
**RECEIVED**

Submit this notice in triplicate to the Oil Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commissioner or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

|   |                                     |   |  |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO TEST CASING SHUT-OFF | <input checked="" type="checkbox"/> | NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL |  |
| NOTICE OF INTENTION TO CHANGE PLANS         |                                     | NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING |  |
| NOTICE OF INTENTION TO REPAIR WELL          |                                     |   |  |
| NOTICE OF INTENTION TO DEEPEN WELL          |                                     | NOTICE OF INTENTION TO PLUG WELL                      |  |

Monument, New Mexico

December 29, 1939.

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the \_\_\_\_\_  
**Amerada Petroleum Corporation** State **LA** Well No. **6** in **NW 1/4 of NE 1/4**  
 Company or Operator **17s** Lease **36e** South Lovington  
 of Sec. **1**, T. **17s**, R. **36e**, N. M. P. M., \_\_\_\_\_ Field,  
 \_\_\_\_\_ County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**

~~FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.~~  
 This well has been drilled to a depth of 4595' and 5 1/2" seamless casing has been set @ 4589' and cemented with 150 sacks of El Toro common and 50 sacks of Quickset cement. The plug was pumped to 4523' @ 8 p.m. December 27, 1939.

We propose to allow this well to stand undisturbed for a period of 72 hours. After this time, pump pressure of 1200# will be applied to the pipe and connections, the valves closed and the pressure within observed for a period of 30 minutes. If there is no drop in pressure, the cement plug will then be drilled and the same test again applied. If there is no drop in pressure after the second test, drilling will be resumed.

Approved **JAN - 2 1940**, 19\_\_\_\_\_  
 except as follows:

**AMERADA PETROLEUM CORPORATION**

By **J. E. Low**  
 Position **Superintendent**

Send communications regarding well to

Name **J. E. Low**

Address **Monument, New Mexico.**

OIL CONSERVATION COMMISSION,

By **Ray Garbrough**  
**OIL & GAS INSPECTOR**  
 Title \_\_\_\_\_