



## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

WORKS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL		

Monument, New Mexico

November 14, 1941

Place

Date

OIL CONSERVATION COMMISSION,

Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

State LA

Well No. 7

in the

NW $\frac{1}{4}$  of NE $\frac{1}{4}$ 

Company or Operator

Lease

of Sec. 1

T. 17s

R. 36E

N. M. P. M.,

S. Lovington

Field,

Lea

County

The dates of this work were as follows:

Notice of intention to do the work was ~~xxxxxx~~ submitted on Form C-102 on 11-12-41  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well had been drilled to a total depth of 3102'. 7-5/8" 22# BEPE Casing set at 3092' and cemented with 250 sacks of El Toro and 50 sacks of Incor Cement. The plug was pumped to 3048'.

Pump pressure of 1200# was applied to the pipe and connections, valves closed and the pressure with in observed for a period of 30 minutes. There was no drop in pressure. The cement plug was then drilled and the same test again applied without a drop in pressure.

Witnessed by	Paul Myers	Loffland Bros.	Tool Pusher
	Name	Company	Title

Subscribed and sworn to before me this

I hereby swear or affirm that the information given above is true and correct.

14th day of November, 1941

Name

Position Ass't. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My Commission expires 2-21-44

Address Drawer "D", Monument, N.M.

Remarks:

Ray Y. Y. Y. Y.  
Name  
Title