

(Title)

MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON

Representing Amerada Petroleum Corporation Address Drawer D, Monument, New Mexico

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, with the first of the District Office is com-

	Indicate Nature of Report by Checking Be	low
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)
	August 19, 1953	Monument, New Mexico
Following is a report on the work	k done and the results obtained under the heading r	noted above at the
Amerada Petroleum Con (Company or O	peration perator)	State LNAN (Lease)
Rowan Drilling Co., Contract	inc. , Well No. 16	in the NE 1/4 NE 1/4 of Sec. 1
T. 17-8 , R. 36-E , NMPM.,	Lovington - Paddock Pool,	Lea
and approval of the proposed plan 🛺 🗷	(was not) obtained	
6240' Total Depth. I Ran a total of Pumped Plug to cement 3724' or no pressure dro	Lime. Finished drilling 7-7/8" hold 200 Jts of 5-1/2" OD casing set @ 5947'. Max pressure 2100#. Ran (* 78.8% fill. After 24 hours tested op. Drilled cement from 5947' to (* 24 hours tested op. Drilled cement from 5947' to (* 24 hours tested op. Drilled cement from 5947' to (* 24 hours tested op. Drilled cement from 5947' to (* 24 hours tested op. Drilled cement from 5947' to (* 24 hours tested op. Drilled cement from 5947' to (* 24 hours tested op. Drilled cement from 5947').	le 6 6:19 PM, 8/18/53. 6015' W/550 sx. temperature survey - top of sd 5-1/2" casing W/800# - 6015' and washed to bottom
6240' Total Depth. Ran a total of Pumped Plug to cement 3724' or no pressure dreat 6240'. (Operations —	Lime. Finished drilling 7-7/8" how 200 Jts of 5-1/2" (D) casing set @ 5947'. Max pressure 2100#. Ran to 78.8% fill. After 24 hours tested op. Drilled cement from 5947' to 6	le 6 6:19 PM, 8/18/53. 6015' W/550 sx. temperature survey - top of sd 5-1/2" casing W/800# - 6015' and washed to bettom tinued with completion
6240' Total Depth. Ran a total of Pumped Plug to cement 3724' or no pressure dreat 6240'. (Ope operations —	Lime. Finished drilling 7-7/8" how 200 Jts of 5-1/2" OD casing set @ 5947'. Max pressure 2100#. Ran (* 78.8% fill. After 24 hours tested op. Drilled cement from 5947' to (* em hole from 6015' to 6240'). Confidence of the first confidence of the f	le 6 6:19 PM, 8/18/53. 6015' W/550 sx. temperature survey - top of set 5-1/2" casing W/800# - 6015' and washed to bottom timued with completion Corporation Foreman - (Title)

AUG 27 1953

(Date)