

Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling opera-tions, results of shooting well, results of test of casing shut off, result of plugging of well, and other important opera-tions, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate	nature	of	report	by	checking	below.
----------	--------	----	--------	----	----------	--------

REPORT ON BEGINNING DRILLING OPERA- TIONS		REPORT ON F	REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL	X	REPORT ON H ALTERING	ULLING OR OTHER G CASING	WISE
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON I	DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL				
	May	8, 1947	Hobbs, New M	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:		Date		Place
Following is a report on the work done and the resul Stanolind Oil & Gas Co.	its obtai	ned under the head State E Tr	ing noted above at the <b>18</b> Well No. 4	in the
NW/4 Company or Operator	1	Lease T. <b>17-S</b>	, <u>в. <b>36-е</b></u>	, N. M. P. M.,
Lovington Field,		ea		County.
The dates of this work were as follows: Notice of intention to do the work was for here and approval of the proposed plan was to be thep	obtaine	d. (Cross out incom	rrect words.)	19 <b>47</b>
(See Rever	rse S	ide)		
R. L. Gray		Stanolind	Oil & Gas Co.	. Field Eng

Name Name	Company Title
Subscribed and sworn before me this 8th	I hereby swear or affirm that the information given abov is true and correct.
day ofMay, 19_47	_ Name KalphZ/Jenulueksan
Obra ith	PositionField Superintendent
Notary Public	Representing <b>STANOLIND OIL &amp; GAS COMPA</b> Company or Operator
My commission expires 2-23-50	Address
Remarks:	Noy. yurkrough
APPROVED	OIL & Cas Inspector
Date MAY 1 2 1947	Title

On March 30, 1947, workover operations were started. After pulling tubing the Dowell Spinner was run and permeable zones were found at 4640-45, 4831-33, and 4875-80. Ran radioactive log, then perforated formation 4650-60, 4666-71, 4676-87, 4702,12, 4796-4804, 4812-18, 4914-32, 4936-42, 4946-50 with 4 shots per foot. Well was cleaned out to bottom and acidized with 1000 gallons from 4911-52 using electric pilot. Spent acid was swabbed off. Well was then plugged back with Ottowa sand and jel seal to 4818 and acidized with 2000 gallons 4818-4658 using electric pilot. Cleaned out to bottom, reran tubing and swabbed. On April 13, well flowed 14 B0 in 24 hours then died. On April 17, flowed 142 B0 in 7 hours then died. Workover was insuccessful in that it will be necessary to install pumping equipment.