

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL		

**DUPLICATE**

**RECEIVED**  
**HOBB'S OFFICE**

Hobbs, New Mexico      December 9, 1939  
Place      Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
**Stanolind Oil and Gas Company**      **State E Tract 18**      Well No. **4**      in the  
 Company or Operator      Lease  
**C NE NW**      of Sec. **1**      T. **17-S**      R. **36-E**      N. M. P. M.,  
**South Lovington**      Field,      **Lea**      County.

The dates of this work were as follows: **December 8, 1939**

Notice of intention to do the work was ~~received~~ submitted on Form C-102 on **December 7,** 19 **39**  
 and approval of the proposed plan was ~~received~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

At 11:00 A.M. December 8, 48 hours had elapsed since setting 5½" casing at 4541' with 325 sacks cement. At this we tested shutoff in the following manner:

Built up pressure to 1000#, closed valves and held for 30 minutes. Drilled plug, again built up pressure to 1000#, closed valves and held for 30 minutes. Test was OK, and drilling was resumed.

Witnessed by **L.O. Herndon**      **Stanolind Oil and Gas Company**      **Production Foreman**  
 Name      Company      Title

Subscribed and sworn before me this

**11** day of **Dec**, 19 **39**

*[Signature]*

Notary Public

My commission expires **June 1, 1940**

I hereby swear or affirm that the information given above is true and correct.

Name **Laurel Herndon**Position **Field Superintendent**Representing **Stanolind Oil and Gas Company**  
Company or OperatorAddress **Box F, Hobbs, New Mexico**

Remarks:

*[Signature]*  
**Oil & Gas Inspector**  
 Name      Title