

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form O-103
Revised 10-1-77

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

1. Indicate Type of Lease
State Fine

2. State Oil & Gas Lease No.
B-1553

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL OR TO DEEPEN FOR A NEW RESERVOIR.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Name of Lease Name State "E" Tract 18
3. Address of Operator P. O. Box 68, Hobbs, New Mexico 88240	9. Well No. 15
4. Location of Well UNIT LETTER C 330 FEET FROM THE North LINE AND 2310 FEET FROM THE West LINE, SECTION 1 TOWNSHIP 17-S RANGE 36-E N.M.P.M.	10. Field and Pool, or Wildcat Lovington Abo
15. Elevation (Show whether DF, RT, GR, etc.) 3844' RDB	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIATION WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1105.

Propose to PxA as follows: Notify NMOCD 24 hrs. prior to moving in service unit. POH with tbg. and pkr. RIH with CIBP, set at 8200', cap CIBP with 35' of Class 'C' neat cmt. With tbg., spot 25 sxs of Class 'C' neat cmt. from 5827-5673'. With tbg. 25 sxs Class 'C' neat cmt. from 3377-3223'. POH. RIH with 4" casing gun and perf through 7" and 9-5/8" csg. at 500' (TCMT behind 9-5/8" csg. is at 1650'). RIH with cmt retainer and tbg. set retainer at 400'. Establish an injection rate with brine water and circulate cmt. behind 7" csg string. Close valve and circulate cmt. behind 9-5/8" casing string. Cap retainer and POH. Spot 15 sxs Class 'C' neat cmt. surface plug. Erect PxA marker and cap well.

**100' plug @ top of salt--1900' +
Load hole w/10# salt gel

O+5-NMOCD,H 1-J. R. Barnett, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-GCC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: Mary C. Clark TITLE: Assist. Admin. Analyst DATE: 6/7/84

APPROVED BY: Eddie W. Seay TITLE: Oil & Gas Inspector DATE: JUN 12 1984

CONDITIONS OF APPROVAL, IF ANY: