

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

| | | | | | |
|---|--|---|----------|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | X | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF PLUGGING WELL | | REPORT ON RECOMPLETION OPERATION | | REPORT ON (Other) | |

October 17, 1952

(Date)

Hobbs, New Mexico

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company

(Company or Operator)

State E, Tract 18

(Lease)

Lee Drilling Company

(Contractor)

Well No. 15 in the NE 1/4 NW 1/4 of Sec. 1

T. 17-S, R. 36-E, NMPM, Lovington-Abo Pool, Lea County.

The Dates of this work were as follows: October 15-17, 1952

Notice of intention to do the work ~~(was)~~ (was not) submitted on Form C-102 on _____, 19____, (Cross out incorrect words)and approval of the proposed plan ~~(was)~~ (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On October 17, 1952 and 10:00 P.M. 48 hours had elapsed since running 3288' of new 9-5/8" casing landed at 3300' and cemented in two stages as follows:

1st Stage: Cemented with 150 sacks regular cement.

2nd Stage: Cemented through staging tool set at 2061' with 150 sacks regular cement.

(Temperature survey indicated top of cement at 1650')

Casing shut off was tested with 1050 psi for 30 minutes before and after drilling staging tool and 1000 psi for 30 minutes after drilling shoe. Since there was no appreciable drop in pressure on any test drilling operations were resumed.

Witnessed by A. C. Blackburn Stanolind Oil and Gas Company Head Roustabout
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

Ray Yarbrough
(Name)

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name Reep H. HennrichPosition Field SuperintendentRepresenting Stanolind Oil and Gas CompanyAddress P.O. Box 68 - Hobbs, New Mexico