NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WEL

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work therifield is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-officients, of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

March 10, 1953 Hobbs, New Mexico

(Cross out incorrect words)

111

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company (Company or Operator)	State "E" Tract 18
Lee Drilling Company (Contractor)	, Well No17in theSE1/4NW1/4 of Sec1
T. 17-S, R. 36-E, NMPM, Lovington - Abo	
The Dates of this work were as folows: March	53
Notice of intention to do the work (was lot) submitted on Form	a C-102 on

and approval of the proposed plan/ (w/s) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On March 7, 1953, at 8:30 A.M. 36 hours had elapsed since running 3283' of new 9-5/8" casing landed at 3296 and cemented in two stages as follows:

1st Stage: Cemented with 150 sacks neat cement.

2nd Stage: Cemented with 150 sacks neat cement. (Temperature survey indicated top of cement at 1550').

Casing shut off was tested with 1000 psi for 30 minutes before and 1050 psi for 30 minutes after drilling DV tool and 1050 psi for 30 minutes after drilling shoe. Since there was no appreciable drop in pressure on any test drilling operations were resumed.

Witnessed by A. C. Blackburn Stanolind	Oil and Gas Company Head Roustabout
Approved: OIL CONSERVATION COMMISSION Non Mulh Olly (Name) (Date)	I hereby certify that the information given above is true and complete to the best of my knowledge. Name