

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, results of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 23, 1953
(Date)Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Stanolind Oil and Gas Company
(Company or Operator)State E Tract 18
(Lease)Lee Drilling Company
(Contractor)

Well No. 19 in the SW/4 NW/4 of Sec. 1

T. 17-S, R. 36-E, NMPM, Lovington-Abo Pool, Lea County.

The Dates of this work were as follows: June 20, 1953 to June 22, 1953

Notice of intention to do the work (☒) (was not) submitted on Form C-102 on _____, 19____, and approval of the proposed plan (☒) (was not) obtained.
(Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On June 20, 1953 ran 3286' of 9-5/8" casing landed at 3298' with DV tool at 2072' and cemented in two stages as follows:

- 1st Stage: Cemented with 150 sacks neat cement.
2nd Stage: Cemented with 150 sacks neat cement.

Temperature survey indicated top of cement at 1537'. After 30 hours WOC tested 9-5/8" casing before drilling DV tool for 30 minutes with 1050 psi with no drop in pressure. Drilled DV tool and tested casing for 30 minutes with 1050 with no drop in pressure. Drilled float collar and 85' of good cement to bottom of shoe. Tested casing for 30 minutes with 1075 psi and as there was no drop in pressure, drilling operations were resumed.

Witnessed by C. D. Harvey (Name) Stanolind Oil and Gas Company (Company) Head Roustabout (Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: *Reed K. Lemmons*

Position: Field Superintendent

Representing: Stanolind Oil and Gas Company

Address: Box 68, Hobbs, New Mexico

Oil & Gas Inspector

JUN 29 1953

(Title)

(Date)