

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in **TRIPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) <b>Convert to SND Well</b>	<input checked="" type="checkbox"/>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)October 28, 1959  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the The Ohio Oil Company'sState "B" 4286 "A"  
(Company or Operator)Well No. 2 in F (Unit)SE 1/4 NW 1/4 of Sec. 2, T. 17-S, R. 36-E, NMPM, Lovington - Abo Pool  
Lea County.FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Total Depth 8530'; 5 1/2" csg. at 8528' with 1400 sacks; 9 5/8" csg. at 3318' with 1750 sacks and 13 3/8" csg. at 349' with 450 sacks. Plugged and abandoned as follows: Bridge plug set at 6320' with 10' cement on top of plug. Cement plug 6115' - 6205' in 5 1/2" csg.; cut off 5 1/2" csg. at 4200' and pulled 5 1/2 csg. Cement plug 4145' - 4245'; cement plug 3270' - 3370' and cement plug 0' - 25'. Proposed work is to drill out cement plugs 0' - 25', 3270' - 3370' and 4145' - 4245'. Clean out to approx. 6000'. Set Baker C.I. bridge plug at 6000' with 10' cement on top of plug. Set retainer type packer on 2 1/2" tbg. at approx. 5500' and perf. lower San Andres section. Treat perf. with 5,000 gal. acid and run injectivity tests. Connect up salt water gathering system to disposal well. Application to convert State B - 4286 "A" Well No. 2, to a salt water disposal well approved by New Mexico Oil Conservation Commission Order R-1500, Dated October 19, 1959.

Approved.....  
Except as follows:....., 19.....Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

THE OHIO OIL COMPANY  
Company or Operator

By.....

Position.....  
Send Communications regarding well to:

Name.....

Address.....

**DISTRIBUTION:**

**NMCC**

**Commissioner of Public Lands**

**Mr. J. A. Grimes**  
**Mr. L. H. Shearer**  
**Mr. D. V. Kitley**  
**Mr. T. A. Steele**  
**Mr. T. O. Webb**  
**Mr. R. E. Feather**