NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin, A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission tional instructions in the Rules and Regulations of the Commission.

		Indicate Nature of Notice	by Checking B	slow	
Notice of Intention to Change Plans		Notice of Intention to Temporarily Abandon We	ELL	Notice of Intention to Drill Deeper	
Notice of Intention to Plug Well		Notice of Intention to Plug Back	X	Notice of Intention to Set Liner	
Notice of Intention To Squeeze		Notice of Intention to Acidize	x	Notice of Intention to Shoot (Nitro)	
Notice of Intention to Gun Perforate	X	Notice of Intention (Other)		Notice of Intention	
OIL CONSERVATION COMMI SANTA FE, NEW MEXICO	SSION	Hobbs, New Mexic	0	October 2 19	59
Gentlemen:		(FAECE)		(Date)	
State HEN Tract 18 (Company of NW/ 1/4 NE/ 1/4 of Sec				American Petroleum (
T CTE BUDGIVISION)		,, K.W.30	• E ,NMPM.,	Lovington-Aba	Ро
Lea	Cox	intv.			•
4)	OLLOW	L DETAILS OF PROPOS INSTRUCTIONS IN THE 1	ED PLAN OI RULES AND R	WORK	
In order to shut off work is planned:	OLLOW	INSTRUCTIONS IN THE I	RULES AND R	EGULATIONS)	remedial
In order to shut off work is planned: Set a cast iron Perforate with	format bridg two sh	ion water and increase plug in 7" casing ots per ft., interval	RULES AND R se product	egulations)	nt.
In order to shut off work is planned: Set a cast iron Perforate with Acidize perforate barrels of oil. Put well on process.	format bridg two sh tions	ion water and increase plug in 7" casing ots per ft., interval with 500 gallons 15%	RULES AND R se product at 8380; at 1s, 8287-8; regular at	ivity the following and cap with 10' comes 289, 8301-8311.	nt. 10-15
In order to shut off work is planned: Set a cast iron Perforate with Acidize perforate barrels of oil. Put well on processors	format bridg two sh tions	ion water and increase plug in 7" casing ots per ft., interval with 500 gallons 15%	se product at 8380' at 8287-8; regular ac	ivity the following indicap with 10' cemer 289, 8301-8311. Edd. Overflush with	nt. 10-15
In order to shut off work is planned: Set a cast iron Perforate with Acidize perforate barrels of oil. Put well on process.	format bridg two sh tions	ion water and increase plug in 7" casing ots per ft., interval with 500 gallons 15%	se product at 8380' at 8380' at 8380' at 8380' at 8387-8 regular ac Crimel Signature American Crimel Signature American American Supplies Supplie	ivity the following indicap with 10' cemer 289, 8301-8311. Edd. Overflush with	nt. 10-15
In order to shut off work is planned: Set a cast iron Perforate with Acidize perforat barrels of oil. Put well on proceed. Accept as follows:	format bridg two sh tions	ion water and increase plug in 7" casing ots per ft., interval with 500 gallons 15%	se product at 8380' at 8380' at 8380' at 8380' at 8387-8 regular ac Crimel Signature American Crimel Signature American American Supplies Supplie	ivity the following of cap with 10' cemer 289, 8301-8311. Eid. Overflush with Corporation	nt. 10-15