

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED

FEB - 1951

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	<b>X</b>	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Odessa, Texas

February 1, 1951

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Trebol Oil Company &amp; E. G. Rodman

State B

Well No. 3

in the

Company or Operator

Lease

SE 1/4 SW 1/4

of Sec. 5

T. 17-S

R. 36-E

N. M. P. M.,

West Lovington

Field,

Lea

County.

The dates of this work were as follows: January 27, 1951

Notice of intention to do the work was (was ~~not~~) submitted on Form C-102 on January 25, 1951and approval of the proposed plan was (was ~~not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The above well was deepened from an old total depth of 5070' to 5140'. A sweet formation packer was set at 5073' and the section from 5073' to 5140' was acidized with 2000 gallons of 20% acid by Western Company. A swabbing test of this interval indicated a production rate of 3 barrels of oil per hour. The section from 4723' to 5073' was then acidized with 3000 gallons and a subsequent swabbing test of this interval indicated a production of 6 barrels of oil per hour. Packer was pulled and tubing run to 5135'. Rods and pump were run with pump set at 5105'. Subsequent pumping test indicates a settled production rate of 78 barrels of oil per day. As a result of this work, production was increased from 22 to 78 barrels per day. Trebol Oil Company & E.G. Rodman, Engineer,

Witnessed by

Name

Company

Title

Subscribed and sworn before me this 1st.

I hereby swear or affirm that the information given above is true and correct.

day of February, 1951

Name M. T. Johnson

Position Engineer

Representing Trebol Oil Company & E. G. Rodman  
Company or Operator

My commission expires June 1, 1951

Address Box 3908, Odessa, Texas

Remarks:

Roy J. Hargrave

Oil &amp; Gas Inspector

Title

