STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

40. OF COPIES ACCEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR	7	

OIL CONSERVATION DIVISION

DISTRIBUTION	P. O. BOX 2088	Form C-103	
SANTA FE	SANTA FE, NEW MEXICO 87501	Revised 10-1-78	
FILE	Sitter of the markets of sol	5a, Indicate Type of Lease	
U.S.G.S.		ا اشعا ا	
LAND OFFICE			
OPERATOR		5. State Oil & Gas Lease No.	
		B-4120	
SUNDR	Y NOTICES AND REPORTS ON WELLS		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)			
1.		7. Unit Agreement Name	
OIL GAS WELL OTHER-		West Lovington Unit	
Name of Operator		8. Farm or Lease Name	
		West Lovington Unit	
EXACO Inc. 3. Address of Operator		9. Well No.	
		52	
P. O. Box 728, Hobbs, New Mexico 8821-0			
4. Location of Well C 1080 North 1080		10.Field and Pool, or Wildcat Lovington San Andres West	
UNIT LETTER G 1980 FEET FROM THE NORth LINE AND 1980 FEET FROM		TITITITI MORT	
Frat	7 17.0 26 0		
THE EBST LINE, SECTION 7 TOWNSHIP 17-S RANGE 36-E NMPM		MPM. (

	15. Elevation (Show whether DF, RT, GR, etc.)	12. County	
	4002° (DF)	Lea ()))))))	
The Check	Appropriate Box To Indicate Nature of Notice, Report of	r Other Data	
		JENT REPORT OF:	
1101152 5. 11.			
[-]	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING	
r		PLUG AND ABANDOHMENT [A]	
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB	, —	
	OTHER		
OTHER			
17 December Descripted on Completed On	perations (Clearly state all pertinent details, and give pertinent dates, incl	uding estimated date of starting any proposed	
work) SEE RULE 1103.	erations (arear) state are personally and grow portrolled		
1. Rigged up. Install H	ROD.		
2. Spot 25 Sx. Cement pl	ug 170M 4004 - 5703 .		
3. Cut $5\frac{1}{2}$ " csg @ 2695' 8			
4. Spot 65 sx. cement pl			
5. Spot 30 sx. Cement pl	ug from 2047'-1946 .		
6. Perforate 8 5/8" csg	W/4-JS @ 350'. Set Cement retainer @ 229'.		
Cement to surface thr	rough 6 5/8" cag perfs. @ 350' W/200 ax. class	'H' Cement.	
8. Spot 30 sx. cement pl	ug fro 100'-surface.		
9. Install dry hole mark			
10. Well plugged and aban			
	•		
•			
18. I hereby certify that the information	above is true and complete to the best of my knowledge and belief.		

SEP 13 1983

O.C.D. HOBBS OFFICE

JUN 29 1983

RECEIVED