					ATTON O	ON'MISSION	
'.	17 6 5			anta Fe, New			
	CATT	N	OTICE O	F INTENT	ON TO DE	211.1	
Notice mu begins. If returned to	st be given to	the Oil Co proposed pl Submit this	nservation lan are con	Commission or sidered advisa	its proper age	ent and approval obta	uch changes will be
	AXAS COMO				ATA	Gratesha	
	SERVATION C	•		the second s	ace	SCOUBEDC	Date 1948
Santa Fe, 1	New Mexico,		',				
Gentlemen:		modified at a			_		
The Ter	cas Compa	nuris Sha	te of	ntention to co	mmence the dr	illing of a well to be Well No3	known as
	Cômp	ny or Operato:	Г Бийн - 11		Lease	Well No.	in
of Sec		/**S, R	<u>36-</u> ,	N. M., P. M.,	Nov	5011 Field, Loa	County.
	N	The (E)	well is <u>i</u>	190 feet	(Ng) (S.) of t	he north line a	and 660 feet
		(12.)				egal subdivision lines	
							_
		lf st	ate land the	e oil and gas l	ease is No. 📃	4287 Assignmen	t No.
						\$10	
		Addr	·ess				-
		The	lessee is	Man Dam	a Common		
		1061				V	
LOCATE W	A 640 ACBES RLL COBRECTI of a bond fo	Addr Ly Weg or this well	ress <u>l}</u> propose to d in conform	IX 2338 H	lrilling equipme le 39 of the	ent as follows: Ro	tary
LOCATE W The status Commission DCON I We propose	of a bond for is as follows i of with to use the fol	Addr We r or this well Clowing string	in conform	ance with Ru of surof and to land on	le 39 of the	ent as follows: Ro General Rules and D Maryland Ca. as indicated:	tary
LOCATE W The status Commission DCON I We propose Size of Hole	of a bond for is as follows i of with to use the fol Size of Casing	Addr Ly We j	in conform	ix 2332 H Irill well with a	le 39 of the	ent as follows: Ro General Rules and 1	tary
LOCATE WI The status Commission Deon 1 We propose Size of Hole 17 ^P	CORRECTION OF A bond for a bond for a follows i of with the follows the follows between the follows size of	Addr We r or this well Clowing string	in conform	ance with Ru ot suppt	buston, i Irilling equipme le 39 of the <u>Jourd of</u> cement them	ent as follows: Ro General Rules and I Maryland Ca as indicated: Landed or	Regulations of the sualty Co., has
LOCATE WI The status Commission Deon 1 We propose Size of Hole 17 ^P 11 [*] 7-7/8 [#] If changes in the first pro Additional in Top of a Suse of Cop of a	RLL CORRECTION of a bond for is as follows i of with to use the fol sto use the fol size of Casing 13-3/8" 8-5/8" 5-1/2" n the above pla oductive oil or nformation: anhydrite Salt	Addr We y or this well <u>State</u> (owing string) Weight Per 48 32 17 In become add gas sand sho FORMATION	visable we vould occur	ance with Ru of suret and to land or New or Second Hand New New New New New New New New Second Hand New New New New Second Hand New New New New Second Hand New New New Second Hand Second Hand New New New Second Hand Second Hand New New Second Hand Second Hand New New Second Hand Second Hand Se	Diston, 1 Irilling equipme le 39 of the <u>bond of</u> cement them Depth 230' 2000' 475C' before cement about 47	exage ent as follows: Ro General Rules and 1 Maryland Ca as indicated: Landed or Comented Comented Comented Comented Comented	Regulations of the Bualty Co., has Comment 250 450 450 450 450 450
LOCATE WI The status Commission Deon 1 We propose Size of Hole 17 ^P 11" 7-7/8" if changes in the first pro Additional in Suse of Cop of a Approved	RLL CORRECTION of a bond for is as follows i of with to use the fol sto use the fol size of Casing 13-3/8" 8-5/8" 5-1/2" n the above pla oductive oil or nformation: Salt	Addr We y or this well <u>State</u> (owing string) Weight Per 48 32 17 In become add gas sand sho FORMATION	ress propose to d in conform D blan Beclogi s of casing Foot visable we would occur	ance with Ru ot suret and to land or New or Becond Hand New New New Well notify you at a depth of CHED 19507 3000 ! 4450 f Sincer	Diston, 1 Irilling equipmed le 39 of the bond of cement them Dopth 250 1 2000 1 475C 1 before cement about 47 Company For TEXAS C	exage ent as follows: Ro General Rules and 1 Maryland Ca as indicated: Landed or Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented	Regulations of the Bualty Co., has Comment 250 450 450 450 450 450
LOCATE WI The status Commission Deon 1 We propose Size of Hole 17 ^P 11 [*] 7-7/8 [#] If changes in the first pro Additional in Top of a Suse of Cop of a	RLL CORRECTION of a bond for is as follows i of with to use the fol sto use the fol size of Casing 13-3/8" 8-5/8" 5-1/2" n the above pla oductive oil or nformation: anhydrite Salt	Addr We y or this well <u>State</u> (owing string) Weight Per 48 32 17 In become add gas sand sho FORMATION	ress propose to d in conform D blan Beclogi s of casing Foot visable we would occur	ance with Ru ot suret and to land or New or Becond Hand New New New Well notify you at a depth of CHED 19507 3000 ! 4450 f Sincer	Diston, T Irilling equipmed le 39 of the bornd of cement them Depth 250 ' 2000 ' 475C ' before cement about 4'7 cely yours, For TEXAS C	exage ent as follows: Ro General Rules and 1 <u>Aryland Ca</u> as indicated: <u>Landed or Comented</u> Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented	Regulations of the Bualty Co., has Comment 250 450 450 450 450 450
LOCATE WI The status Commission Deen 1 We propose Size of Hole 17 ^B 11 ^S -7/8 ^S f changes in he first pro Additional in 50 of a hpproved except a	RLL CORRECTION of a bond for is as follows i of with to use the fol size of Casing 13-3/3" 8-5/8" 8-5/8" 5-1/2" n the above play oductive oil or information: anhydrite Sait sain Brow as follows SE ^c	Addr We y or this well <u>State</u> towing string Weight Per 48 32 17 an become add gas sand sho PORCA STO 7 1948	ress propose to d in conform 2 blan S of casing Foot visable we would occur S 120 , 19,	ance with Ru ance with Ru and to land or Becond Hand New New New New New New Score for Socor for 4450 f Sinces	Distor, T Irilling equipmed le 39 of the bornd of cement them Depth 250 ' 2000 ' 475C ' before cement about 47 Can rely yours, For TEXAS C	ent as follows: Ro General Rules and D Maryland Ca as indicated: Landed or Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Coment	Regulations of the Sualty Co., has Socks Cement 250 450 450 450 450 450 450 450 4
LOCATE WI The status Commission Decen 1 We propose Size of Hole 17 ^B 11 ⁹ 7-7/8 ³ I changes in the first pro Additional in top of a hpproved except a	RLL CORRECTION of a bond for is as follows i of with to use the fol sto use the fol size of Casing 13-3/8" 8-5/8" 5-1/2" n the above pla oductive oil or nformation: anhydrite Salt	Addr We y or this well <u>State</u> towing string Weight Per 48 32 17 an become add gas sand sho PORCA STO 7 1948	ress propose to d in conform 2 blan S of casing Foot visable we would occur S 120 , 19,	ance with Ru ance with Ru and to land or Rew or Second Hand New New New New New New New New	Distor, 1 Irilling equipmed le 39 of the bord of cement them Depth 250 1 2000 1 475C 1 before cement about 47 Can rely yours, For TEXAS Con mAssistates	exage ent as follows: Ro General Rules and I Maryland Ca as indicated: Landed or Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Com	Regulations of the Sualty Co., has Socks Cement 250 450 450 450 450 450 450 450 4
LOCATE WI The status Commission Decen 1 We propose Size of Hole 17 ^B 11 ⁹ 7-7/8 ³ I changes in the first pro Additional in top of a hpproved except a	RLL CORRECTION of a bond for is as follows i ed with to use the fol size of Casing 13-3/3" 8-5/8" 8-5/8" 5-1/2" n the above play oductive oil or nformation: anhydri te Sait Main Brow as follows: SEP	Addr We y or this well <u>State</u> towing string Weight Per 48 32 17 an become add gas sand sho PORCA STO 7 1948	ress propose to d in conform 2 blan S of casing Foot visable we would occur S 120 , 19,	ance with Ru ance with Ru and to land or New or Second Hand New New New New New New New New	Distor, i rilling equipmedia le 39 of the bond of cement them Dopth 250 1 2000 1 475C 1 before cement about 47 Can rely yours, For TEXAS C	exps ent as follows: Ro General Rules and 1 <u>Aryland Ca</u> as indicated: <u>Landed or Comented</u> Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented Comented C	Regulations of the Sualty Co., has Socks Cement 250 450 450 450 450 450 450 450 4