

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

|   |  |   |                                     |                          |  |
|---|--|---|-------------------------------------|--------------------------|--|
| REPORT ON BEGINNING DRILLING OPERATIONS |  | REPORT ON RESULT OF TEST OF CASING SHUT-OFF | <input checked="" type="checkbox"/> | REPORT ON REPAIRING WELL |  |
| REPORT ON RESULT OF PLUGGING WELL       |  | REPORT ON RECOMPLETION OPERATION            |                                     | REPORT ON (Other)        |  |

March 16, 1953

(Date)

Hobbs, N. M.

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil &amp; Refining Company

(Company or Operator)

New Mexico State T

(Lease)

Gackle Drilling Company

(Contractor)

Well No. 2 in the NE 1/4 of Sec. 8

T. 17S, R. 36E, NMPM., W. Lovington Pool, Lea County.

The Dates of this work were as follows: 3-13-53

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on \_\_\_\_\_, 19\_\_\_\_, (Cross out incorrect words)

and approval of the proposed plan (was) ~~not~~ obtained.

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Ran 166 Jts. 5-1/2" casing, 5068', set at 5080', cemented with 1050 sacks 10% gel cement. Job completed 7:35 A. M. 3-13-53. Cement circulated approx. 15 sacks to surface. Rotated while cementing.

Tested 5-1/2" casing at 1:35 P. M. 3-14-53 with 1000# for 30 minutes. Test OK. No drop in pressure. Drilled plug to 5078'. Displaced mud with oil.

Witnessed by E. D. Walcott  
(Name)

Humble Oil & Refining Company  
(Company)

Tool Pusher  
(Title)

Approved:

OIL CONSERVATION COMMISSION

Roy Garbrough  
(Name)

(Title)  
mcb/mcb

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

Position

Representing

Address

E. D. Walcott

District Superintendent

Humble Oil &amp; Refining Co.

Box 2347, Hobbs, N. M.