

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

Midland, Texas

March 22, 1945

Place

Date

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Humble Oil & Refining Co. New Mexico State P Well No. 4 in the  
Company or Operator Lease

SW/4 of NW/4 of Sec. 9, T. 17-S, R. 36-E, N. M. P. M.,  
West Lovington Field, Lea County.

The dates of this work were as follows: March 18th, 19th, and 20th, 1945

Notice of intention to do the work was ~~consent~~ submitted on Form C-102 on March 19, 1945 19  
and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

The well was plugged as follows: 135 sacks of Line Star cement was placed in the bottom of the hole from 5100' to 4500'. The hole was then filled with mud from 4500' to 1980'. An 8 1/2 sack cement plug was then placed in the bottom of the 7-5/8" casing from 1980' to 1780'. 6 joints of 7-5/8" casing (244.35') was recovered. The hole was filled with mud to top and a cement plug consisting of 10 sacks of Line Star cement was placed in the top of the 10-3/4" casing. Bull plug was placed on top and the hole was identified by suitable marker as required by the regulations of the New Mexico Oil Conservation Commission.

Witnessed by \_\_\_\_\_ Name \_\_\_\_\_ Company \_\_\_\_\_ Title \_\_\_\_\_

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

24th day of March, 19 45Name [Signature]Position Division Superintendent.

Representing Humble Oil & Refining Co.  
Company or Operator

My commission expires 6-1-45.Address Box 1600, Midland, Texas.

Remarks:

Roy Gardner  
Name  
Title