

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		Notice of Intention to Plug and Abandon.	

Midland, Texas

March 19, 1945

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Humble Oil & Refining Company New Mexico State P Well No. 4 in SW/4 of NW/4
Company or Operator Lease
of Sec. 9, T. 17-S, R. 36-E, N. M. P. M., West Lovington Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Halliburton Drill Stem test was taken from 4727' to 4950'. The tool was open 2 hours. Recovered 330' of water cut mud and 841 feet of sulphur water. Another drill stem test was made from 4950' to 5100'. The tool was left open for 1 hour and 33 minutes. Well made 3300' of sulphur water and mud through 5/8" choke. The drill stem tests as shown above indicated the well could not be made into a producer and decision was made to plug and abandon the well. The proposed plan is as follows: Will place cement plug from 5100' to 4950' using 135 sacks of cement. Hole will be mudded to the bottom of the 7-5/8" casing which is set at 1978'. A 200' cement plug will be placed in the bottom of the 7-5/8" casing and the hole will be mudded to the bottom of the 10-3/4" casing set at 326'. A 100' cement plug will be placed in the bottom of the 10-3/4" casing and the hole mudded up to 25' of the top of the hole. A 25' plug will be placed in the top of the 10-3/4" casing and a bull plug placed in the top of the hole. As much as possible of the 7-5/8" casing will be recovered. Suitable marker will be placed in accordance with plugging regulations of the Commission.

Approved _____, 19____
except as follows:

OIL CONSERVATION COMMISSION,

By Roy Yarrrough
Title _____

Humble Oil & Refining Company

Company or Operator

By [Signature]
Position Division Superintendent.

Send communications regarding well to

Name J. W. House.Address Box 1600, Midland, Texas.