

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

		REPORT ON	REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL		REPORT ON ALTERIN	PULLING OR OTHER	WISE
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON	DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	I			
	Midla	nd, Texas	May 23,	1945
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:		Place		Date
Following is a report on the work done and the resu Humble Oil & Refining Company N.	M. St	ate "R"	ding noted above at the Well No	
NE/4 of NE/4 of Sec	9	1753	36-E	in the
lest Lovington Field	,	T. LOR	, R	, N. M. P. M.
The dates of this work were as follows:	-19, 1	945		County
Notice of intention to do the work was (was not) su	hmitted	on Form C 109 on	March 16	19
Loaded hole with mud. Placed 35 sac casing off and pulled 57 joints, 248 to 1800'. Shot 7-5/8" casing off and cement plug from 300' to 150'. Dump	1.82'. pulle	nt plug from Placed 75 s d 4 joints, 1	ack cement plug i .29.70'. Placed '	rom 2000† 50 sack
casing off and pulled 57 joints, 248 to 1800'. Shot 7-5/8" casing off and cement plug from 300' to 150'. Damp regulation well marker.	1.82'. pulle	nt plug from Placed 75 s d 4 joints, 1	4785' to 4499'. S ack cement plug 1 .29.70'. Placed 4	rom 2000† 50 sack
casing off and pulled 57 joints, 248 to 1800'. Shot 7-5/8" casing off and cement plug from 300' to 150'. Damp regulation well marker.	1.82'. pulle	nt plug from Placed 75 s d 4 joints, 1	4785' to 4499'. S ack cement plug i .29.70'. Placed y in top and instal	rom 2000*
Casing off and pulled 57 joints, 248 to 1800'. Shot 7-5/8" casing off and cement plug from 300' to 150'. Dump regulation well marker. Witnessed by	1.82'. pulle ed 25	nt plug from Placed 75 a d 4 joints, 1 sacks coment Company hereby swear or s true and correct.	4785' to 4499'. S ack cement plug i .29.70'. Placed y in top and instal	Title
casing off and pulled 57 joints, 248 to 1800'. Shot 7-5/8" casing off and cement plug from 300' to 150'. Dump regulation well marker. Witnessed by	1.82'. pulle ed 25 is 1 is	nt plug from Placed 75 a d 4 joints, 1 sacks coment Company hereby swear or s true and correct. Iame	4785' to 4499'. S lack cement plug i .29.70'. Placed y in top and instal affirm that the informa	Title
Casing off and pulled 57 joints, 248 to 1800'. Shot 7-5/8" casing off and cement plug from 300' to 150'. Dump regulation well marker. Witnessed by	1.82'. pulle ed 25 is 45 N	nt plug from Placed 75 a d 4 joints, 1 sacks cement Company hereby swear or s true and correct. Jame	4785' to 4499'. S ack cement plug i .29.70'. Placed y in top and instal affirm that the informa	Title Title
Casing off and pulled 57 joints, 248 to 1800'. Shot 7-5/8" casing off and cement plug from 300' to 150'. Dump regulation well marker. Witnessed by	1.82'. pulle ed 25 I is 45 N P R	Company hereby swear or strue and correct. Tame cosition	4785' to 4499'. S lack cement plug i .29.70'. Placed y in top and instal affirm that the informa 	Title Title tion given above