

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

AUG 23 8 19 AM '65

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>

5. State Oil & Gas Lease No.

NM 103

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Exploratory		7. Unit Agreement Name
2. Name of Operator Sinclair Oil & Gas Company		8. Farm or Lease Name State M
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER O 1980 FEET FROM THE East LINE AND 990 FEET FROM THE South LINE, SECTION 17 TOWNSHIP 17S RANGE 36E NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3877' GR		12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-39-62 Spudded 17 1/2" hole.
4-2-62 Ran 357' of 12-3/8" 54# Casing and cemented w/375 sacks cement. Cement Circulated. WOC 24 hrs. Pressure tested casing to 1000# for 30 min. Tested OK.
4-7-62 Ran 3600' of 8-5/8" OD 30# and 24# J-55 casing and cemented w/200 sacks neat cement. WOC 24 hrs. Pressure tested casing to 1000# for 30 min. Tested OK.
5-15-62 Total Depth 9316'.
5-16-62 Set plugs to plug and abandon as follows: 9250-9115' w/40 sacks, 7300-7233' w/20 sks, 6400-6332' w/20 sks, 3641-3518' w/25 sks. Cut 8-5/8" esg @ 1507' and set cement plug across out 1470-1520' w/20 sks, 344-372' w/20 sks. and 0-13' w/10 sks. Welded plate on top of 12-3/8" casing and installed marker.

Note: This well was previously operated by Texas Gulf Producing Company and has been acquired by Sinclair Oil & Gas Company.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE **Superintendent** DATE **8-20-65**

APPROVED BY [Signature] TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Orig&2cc: OCC Hobbs, cc: RFC, cc: file